



CAR MAP

AERONAUTICAL CHARTS

FOREWORD

CONTENTS

REVISION RECORD

LIST of EFFECTIVE PAGES



This Page Intentionally Left Blank



FOREWORD

1. The Civil Aviation Authority Bahamas is known in these regulations as the “Authority” and has implemented CAR MAP, (Civil Aviation Regulations – Aeronautical Charts). The regulations are made under the Civil Aviation Authority Act - 2021.
2. Other regulations involving Air Navigation Services are;
 - (a) CAR ATS – Air Traffic Services
 - (b) CAR CNS - Aeronautical Communications
 - (c) CAR MET – Aviation Meteorology Services
 - (d) CAR AIS - Aeronautical Information Services
 - (e) CAR SAR - Search and Rescue
 - (f) CAR IFPD – Instrument Flight Procedures and Design Services
3. Unless otherwise stated, applicable CAR DEF definitions, abbreviations and units of measurement are used throughout this document.
4. Any reference in this regulation to an Annex to the Chicago Convention includes any differences, present or future, notified to ICAO by the Authority in respect of the Standards specified in that Annex.
5. The editing practices used in this document are as follows;
 - (a) ‘Shall’ or ‘Will’ or ‘Must’ is used to indicate a mandatory requirement.
 - (b) ‘Should’ is used to indicate a recommendation.
 - (c) ‘May’ is used to indicate discretion by the Authority, the industry or the applicant, as appropriate.

Note: The use of the male gender implies all genders.

6. [Paragraphs and sub-paragraphs with new, amended and corrected text will be enclosed within square brackets until a subsequent “amendment” is issued.]



REVISION RECORD

REVISION NO.	EFFECTIVE DATE	ENTERED BY <i>(Hardcopy only)</i>
Initial Issue	25 March 2021	
Revision 01	01 July 2021	



LIST OF EFFECTIVES PAGES

i	01 Jul 21	5-5	25 Mar 21	12-3	25 Mar 21
ii	01 Jul 21	5-6	25 Mar 21	12-4	25 Mar 21
iii	01 Jul 21				
iv	01 Jul 21				
v	01 Jul 21				
vi	01 Jul 21				
vii	01 Jul 21				
viii	01 Jul 21				
ix	01 Jul 21				
x	01 Jul 21				
Chapter 1		Chapter 6		Chapter 13	
1-1	25 Mar 21	6-1	25 Mar 21	13-1	01 Jul 21
1-2	25 Mar 21	6-2	25 Mar 21	13-2	01 Jul 21
1-3	25 Mar 21			13-3	01 Jul 21
1-4	25 Mar 21			13-4	01 Jul 21
1-5	25 Mar 21				
1-6	25 Mar 21				
1-7	25 Mar 21				
1-8	25 Mar 21				
Chapter 2		Chapter 7		Chapter 14	
2-1	25 Mar 21	7-1	25 Mar 21	14-1	01 Jul 21
2-2	25 Mar 21	7-2	25 Mar 21	14-2	01 Jul 21
2-3	25 Mar 21				
2-4	25 Mar 21				
2-5	25 Mar 21				
2-6	25 Mar 21				
Chapter 3		Chapter 8		Chapter 15	
3-1	25 Mar 21	8-1	25 Mar 21	15-1	25 Mar 21
3-2	25 Mar 21	8-2	25 Mar 21	15-2	25 Mar 21
3-3	25 Mar 21	8-3	25 Mar 21		
3-4	25 Mar 21	8-4	25 Mar 21		
Chapter 4		Chapter 9		Chapter 16	
4-1	25 Mar 21	9-1	01 Jul 21	16-1	25 Mar 21
4-2	25 Mar 21	9-2	01 Jul 21	16-2	25 Mar 21
4-3	25 Mar 21	9-3	01 Jul 21	16-3	25 Mar 21
4-4	25 Mar 21	9-4	01 Jul 21	16-4	25 Mar 21
Chapter 5		Chapter 10		Chapter 17	
5-1	25 Mar 21	10-1	01 Jul 21	17-1	25 Mar 21
5-2	25 Mar 21	10-2	01 Jul 21	17-2	25 Mar 21
5-3	25 Mar 21	10-3	01 Jul 21	17-3	25 Mar 21
5-4	25 Mar 21	10-4	01 Jul 21	17-4	25 Mar 21
Chapter 6		Chapter 11		Chapter 18	
		11-1	01 Jul 21	18-1	25 Mar 21
		11-2	01 Jul 21	18-2	25 Mar 21
		11-3	01 Jul 21	18-3	25 Mar 21
		11-4	01 Jul 21	18-4	25 Mar 21
		11-5	01 Jul 21	18-5	25 Mar 21
		11-6	01 Jul 21	18-6	25 Mar 21
		11-7	01 Jul 21		
		11-8	01 Jul 21		
Chapter 7		Chapter 12		Chapter 19	
		12-1	25 Mar 21	1-1	25 Mar 21
		12-2	25 Mar 21	1-2	25 Mar 21



Chapter 20

20-1 25 Mar 21
20-2 25 Mar 21

Chapter 21

21-1 25 Mar 21
21-2 25 Mar 21
-End-



CONTENTS

Forewordi
 Revision Recordii
 List of Effective Pages iii
 Contentsv

CHAPTER 1 DEFINITIONS, APPLICABILITY AND AVAILABILITY

1.1 Definitions1-1
 1.2 Applicability1-11
 1.3 Availability1-11

CHAPTER 2 GENERAL SPECIFICATIONS

2.1 Operational requirements for charts2-1
 2.2 Titles2-1
 2.3 Miscellaneous information2-2
 2.4 Symbols2-2
 2.5 Units of measurement2-2
 2.6 Scale and projection2-3
 2.7 Date of validity of aeronautical information2-3
 2.8 Spelling of geographical names2-3
 2.9 Abbreviations2-3
 2.10 Political boundaries2-3
 2.11 Colours2-3
 2.12 Relief2-4
 2.13 Prohibited, restricted and danger areas2-4
 2.14 Air traffic services airspaces2-4
 2.15 Magnetic variation2-4
 2.16 Typography2-4
 2.17 Aeronautical data2-5
 2.18 Common reference systems2-5

CHAPTER 3 AERODROME OBSTACLE CHART - ICAO TYPE A (OPERATING LIMITATIONS)

3.1 Function3-1
 3.2 Availability3-1
 3.3 Units of measurement3-1
 3.4 Coverage and scale3-1
 3.5 Format3-1
 3.6 Identification3-2
 3.7 Magnetic variation3-2
 3.8 Aeronautical data3-2
 3.9 Accuracy3-4

CHAPTER 4 AERODROME OBSTACLE CHART — ICAO TYPE B

4.1 Function4-1
 4.2 Availability4-1
 4.3 Units of measurement4-1
 4.4 Coverage and scale4-1
 4.5 Format4-1



4.6	Identification	4-2
4.7	Culture and topography	4-2
4.8	Magnetic variation.....	4-2
4.9	Aeronautical data	4-2
4.10	Accuracy	4-3

CHAPTER 5 AERODROME TERRAIN AND OBSTACLE CHART — ICAO (ELECTRONIC)

5.1	Function	5-1
5.2	Availability	5-1
5.3	Identification	5-1
5.4	Chart coverage	5-1
5.5	Chart content.....	5-2
5.6	Accuracy and resolution	5-4
5.7	Electronic functionality	5-4
5.8	Chart data product specifications	5-4

CHAPTER 6 PRECISION APPROACH TERRAIN CHART — ICAO

6.1	Function	6-1
6.2	Availability	6-1
6.3	Scale	6-1
6.4	Identification.....	6-1
6.5	Plan and profile information	6-1

CHAPTER 7 ENROUTE CHART — ICAO

7.1	Function	7-1
7.2	Availability	7-1
7.3	Coverage and scale.....	7-1
7.4	Projection.....	7-1
7.5	Identification.....	7-1
7.6	Culture and topography	7-1
7.7	Magnetic variation.....	7-2
7.8	Bearings, tracks and radials	7-2
7.9	Aeronautical data	7-2

CHAPTER 8 AREA CHART — ICAO

8.1	Function	8-1
8.2	Availability	8-1
8.3	Coverage and scale.....	8-1
8.4	Projection.....	8-1
8.5	Identification.....	8-1
8.6	Culture and topography	8-1
8.7	Magnetic variation.....	8-1
8.8	Bearings, tracks and radials	8-2
8.9	Aeronautical data	8-2

CHAPTER 9 STANDARD DEPARTURE CHART — INSTRUMENT (SID) — ICAO

9.1	Function	9-1
9.2	Availability	9-1



9.3	Coverage and scale.....	9-1
9.4	Projection.....	9-1
9.5	Identification.....	9-1
9.6	Culture and topography.....	9-1
9.7	Magnetic variation.....	9-2
9.8	Bearings, tracks and radials.....	9-2
9.9	Aeronautical data.....	9-2

CHAPTER 10 STANDARD ARRIVAL CHART — INSTRUMENT (STAR) — ICAO

10.1	Function.....	10-1
10.2	Availability.....	10-1
10.3	Coverage and scale.....	10-1
10.4	Projection.....	10-1
10.5	Identification.....	10-1
10.6	Culture and topography.....	10-1
10.7	Magnetic variation.....	10-2
10.8	Bearings, tracks and radials.....	10-2
10.9	Aeronautical data.....	10-2

CHAPTER 11 INSTRUMENT APPROACH CHART — ICAO

11.1	Function.....	11-1
11.2	Availability.....	11-1
11.3	Coverage and scale.....	11-1
11.4	Format.....	11-2
11.5	Projection.....	11-2
11.6	Identification.....	11-2
11.7	Culture and topography.....	11-2
11.8	Magnetic variation.....	11-3
11.9	Bearings, tracks and radials.....	11-3
11.10	Aeronautical data.....	11-3

CHAPTER 12 VISUAL APPROACH CHART — ICAO

12.1	Function.....	12-1
12.2	Availability.....	12-1
12.3	Scale.....	12-1
12.4	Format.....	12-1
12.5	Projection.....	12-1
12.6	Identification.....	12-1
12.7	Culture and topography.....	12-1
12.8	Magnetic variation.....	12-2
12.9	Bearings, tracks and radials.....	12-2
12.10	Aeronautical data.....	12-2

CHAPTER 13 AERODROME/HELIPORT CHART — ICAO

13.1	Function.....	13-1
13.2	Availability.....	13-1
13.3	Coverage and scale.....	13-1
13.4	Identification.....	13-1
13.5	Magnetic variation.....	13-1



13.6 Aerodrome/heliport data.....13-1

CHAPTER 14 AERODROME GROUND MOVEMENT CHART — ICAO

14.1 Function14-1
 14.2 Availability14-1
 14.3 Coverage and scale.....14-1
 14.4 Identification.....14-1
 14.5 Magnetic variation.....14-1
 14.6 Aerodrome data.....14-1

CHAPTER 15 AIRCRAFT PARKING/DOCKING CHART — ICAO

15.1 Function15-1
 15.2 Availability15-1
 15.3 Coverage and scale.....15-1
 15.4 Identification.....15-1
 15.5 Magnetic variation.....15-1
 15.6 Aerodrome data.....15-1

CHAPTER 16 WORLD AERONAUTICAL CHART — ICAO 1:1,000,000

16.1 Function16-1
 16.2 Availability16-1
 16.3 Scales.....16-1
 16.4 Format.....16-1
 16.5 Projection.....16-2
 16.6 Identification.....16-2
 16.7 Culture and topography16-3
 16.8 Magnetic variation.....16-4
 16.9 Aeronautical data16-4

CHAPTER 17 AERONAUTICAL CHART — ICAO 1:500,000

17.1 Function17-1
 17.2 Availability17-1
 17.3 Scales.....17-1
 17.4 Format.....17-1
 17.5 Projection.....17-2
 17.6 Identification.....17-2
 17.7 Culture and topography17-2
 17.8 Magnetic variation.....17-4
 17.9 Aeronautical data17-4

CHAPTER 18 AERONAUTICAL NAVIGATION CHART — ICAO SMALL SCALE

18.1 Function18-1
 18.2 Availability18-1
 18.3 Coverage and scale.....18-1
 18.4 Format.....18-1
 18.5 Projection.....18-2
 18.6 Culture and topography18-2
 18.7 Magnetic variation.....18-4



18.8	Aeronautical data	18-4
------	-------------------------	------

CHAPTER 19 PLOTTING CHART — ICAO

19.1	Function	19-1
19.2	Availability	19-1
19.3	Coverage and scale	19-1
19.4	Format.....	19-1
19.5	Projection.....	19-1
19.6	Identification.....	19-1
19.7	Culture and topography	19-1
19.8	Magnetic variation.....	19-2
19.9	Aeronautical data	19-2

CHAPTER 20 ELECTRONIC AERONAUTICAL CHART DISPLAY — ICAO

20.1	Function	20-1
20.2	Information available for display	20-1
20.3	Display requirements.....	20-1
20.4	Provision and updating of data	20-2
20.5	Performance tests, malfunction alarms and indications	20-2
20.6	Back-up arrangements	20-2

CHAPTER 21 ATC SURVEILLANCE MINIMUM ALTITUDE CHART — ICAO

21.1	Function	21-1
21.2	Availability	21-1
21.3	Coverage and scale	21-1
21.4	Projection.....	21-1
21.5	Identification.....	21-1
21.6	Culture and topography	21-1
21.7	Magnetic variation.....	21-1
21.8	Bearings, tracks and radials	21-2
21.9	Aeronautical data	21-2



This Page Intentionally Left Blank



CHAPTER 1

DEFINITIONS, APPLICABILITY AND AVAILABILITY

1.1 Definitions

When the following terms are used in CAR MAP, they have the following meanings:

Aerodrome. A defined area on land or water (including any buildings, installations and equipment) intended to be used either wholly or in part for the arrival, departure and surface movement of aircraft.

Aerodrome elevation. The elevation of the highest point of the landing area.

Aerodrome operating minima. The limits of usability of an aerodrome for:

- (a) take-off, expressed in terms of runway visual range and/or visibility and, if necessary, cloud conditions;
- (b) landing in precision approach and landing operations, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H) as appropriate to the category of the operation;
- (c) landing in approach and landing operations with vertical guidance, expressed in terms of visibility and/or runway visual range and decision altitude/height (DA/H); and
- (d) landing in non-precision approach and landing operations, expressed in terms of visibility and/or runway visual range, minimum descent altitude/height (MDA/H) and, if necessary, cloud conditions.

Aerodrome reference point. The designated geographical location of an aerodrome.

Aeronautical chart. A representation of a portion of the Earth, its culture and relief, specifically designated to meet the requirements of air navigation.

Aircraft stand. A designated area on an apron intended to be used for parking an aircraft.

Air defence identification zone. Special designated airspace of defined dimensions within which aircraft are required to comply with special identification and/or reporting procedures additional to those related to the provision of air traffic services (ATS).

Air traffic service. A generic term meaning variously, flight information service, alerting service, air traffic advisory service, air traffic control service (area control service, approach control service or aerodrome control service).

Air transit route. A defined route for the air transiting of helicopters.

Airway. A control area or portion thereof established in the form of a corridor.

Altitude. The vertical distance of a level, a point or an object considered as a point, measured from mean sea level (MSL).

Application. Manipulation and processing of data in support of user requirements (ISO 19104*).



Apron. A defined area, on a land aerodrome, intended to accommodate aircraft for purposes of loading or unloading passengers, mail or cargo, fuelling, parking or maintenance.

Area minimum altitude (AMA). The minimum altitude to be used under instrument meteorological conditions (IMC), that provides a minimum obstacle clearance within a specified area, normally formed by parallels and meridians.

Area navigation (RNAV). A method of navigation which permits aircraft operation on any desired flight path within the coverage of ground- or space-based navigation aids or within the limits of the capability of self-contained aids, or a combination of these.

Note: Area navigation includes performance-based navigation as well as other operations that do not meet the definition of performance-based navigation.

Arrival routes. Routes identified in an instrument approach procedure by which aircraft may proceed from the en-route phase of flight to an initial approach fix.

ATS route. A specified route designed for channelling the flow of traffic as necessary for the provision of air traffic services.

Note 1: The term ATS route is used to mean variously, airway, advisory route, controlled or uncontrolled route, arrival or departure route, etc.

Note 2: An ATS route is defined by route specifications that include an ATS route designator, the track to or from significant points (waypoints), distance between significant points, reporting requirements and, as determined by the appropriate ATS authority, the lowest safe altitude.

ATS surveillance system. A generic term meaning variously, ADS-B, PSR, SSR or any comparable ground-based system that enables the identification of aircraft.

Note: A comparable ground-based system is one that has been demonstrated, by comparative assessment or other methodology, to have a level of safety and performance equal to or better than monopulse SSR.

Bare Earth. Surface of the Earth including bodies of water and permanent ice and snow, and excluding vegetation and man-made objects.

Calendar. Discrete temporal reference system that provides the basis for defining temporal position to a resolution of one day (ISO 19108*).

Canopy. Bare Earth supplemented by vegetation height.

Change-over point. The point at which an aircraft navigating on an ATS route segment defined by reference to very high frequency omnidirectional radio ranges is expected to transfer its primary navigational reference from the facility behind the aircraft to the next facility ahead of the aircraft.

Note: Change-over points are established to provide the optimum balance in respect of signal strength and quality between facilities at all levels to be used and to ensure a common source of azimuth guidance for all aircraft operating along the same portion of a route segment.

Clearway. A defined rectangular area on the ground or water under the control of the appropriate authority, selected or prepared as a suitable area over which an aeroplane may make a portion of its initial climb to a specified height.



Contour line. A line on a map or chart connecting points of equal elevation.

Culture. All man-made features constructed on the surface of the Earth, such as cities, railways and canals.

Cyclic redundancy check (CRC). A mathematical algorithm applied to the digital expression of data that provides a level of assurance against loss or alteration of data.

Danger area. An airspace of defined dimensions within which activities dangerous to the flight of aircraft may exist at specified times.

Data product specification. Detailed description of a data set or data set series together with additional information that will enable it to be created, supplied to and used by another party (ISO 19131*).

Note: A data product specification provides a description of the universe of discourse and a specification for mapping the universe of discourse to a data set. It may be used for production, sales, end-use or other purpose.

Data quality. A degree or level of confidence that the data provided meet the requirements of the data user in terms of accuracy, resolution and integrity (or equivalent assurance level), traceability, timeliness, completeness and format.

Data resolution. A number of units or digits to which a measured or calculated value is expressed and used.

Data set. Identifiable collection of data (ISO 19101*).

Data set series. Collection of data sets sharing the same product specification (ISO 19115*).

Datum. Any quantity or set of quantities that may serve as a reference or basis for the calculation of other quantities (ISO 19104*).

Digital Elevation Model (DEM). The representation of terrain surface by continuous elevation values at all intersections of a defined grid, referenced to common datum.

Note: Digital Terrain Model (DTM) is sometimes referred to as DEM.

Displaced threshold. A threshold not located at the extremity of a runway.

Electronic aeronautical chart display. An electronic device by which flight crews are enabled to execute, in a convenient and timely manner, route planning, route monitoring and navigation by displaying required information.

Elevation. The vertical distance of a point or a level, on or affixed to the surface of the earth, measured from mean sea level.

Ellipsoid height (Geodetic height). The height related to the reference ellipsoid, measured along the ellipsoidal outer normal through the point in question.

Feature. Abstraction of real world phenomena (ISO 19101*).

Feature attribute. Characteristic of a feature (ISO 19101*).



Note: A feature attribute has a name, a data type and a value domain associated with it.

Final approach. That part of an instrument approach procedure which commences at the specified final approach fix or point, or where such a fix or point is not specified,

- (a) at the end of the last procedure turn, base turn or inbound turn of a racetrack procedure, if specified; or
- (b) at the point of interception of the last track specified in the approach procedure; and ends at a point in the vicinity of an aerodrome from which:
 - (1) a landing can be made; or
 - (2) a missed approach procedure is initiated.

Final approach and take-off area (FATO). A defined area over which the final phase of the approach manoeuvre to hover or landing is completed and from which the take-off manoeuvre is commenced. Where the FATO is to be used by performance Class 1 helicopters, the defined area includes the rejected take-off area available.

Final approach fix or point. That fix or point of an instrument approach procedure where the final approach segment commences.

Final approach segment. That segment of an instrument approach procedure in which alignment and descent for landing are accomplished.

Flight information region. An airspace of defined dimensions within which flight information service and alerting service are provided.

Flight level. A surface of constant atmospheric pressure which is related to a specific pressure datum, 1 013.2 hectopascals (hPa), and is separated from other such surfaces by specific pressure intervals.

Note 1: A pressure type altimeter calibrated in accordance with the Standard Atmosphere:

- (a) when set to a QNH altimeter setting, will indicate altitude;
- (b) when set to a QFE altimeter setting, will indicate height above the QFE reference datum;
- (c) when set to a pressure of 1 013.2 hPa, may be used to indicate flight levels.

Note 2: The terms “height” and “altitude”, used in Note 1 above, indicate altimetric rather than geometric heights and altitudes.

Geodesic distance. The shortest distance between any two points on a mathematically defined ellipsoidal surface.

Geodetic datum. A minimum set of parameters required to define location and orientation of the local reference system with respect to the global reference system/frame.

Geoid. The equipotential surface in the gravity field of the Earth which coincides with the undisturbed mean sea level (MSL) extended continuously through the continents.



Note: The geoid is irregular in shape because of local gravitational disturbances (wind tides, salinity, current, etc.) and the direction of gravity is perpendicular to the geoid at every point.

Geoid undulation. The distance of the geoid above (positive) or below (negative) the mathematical reference ellipsoid.

Note: In respect to the World Geodetic System — 1984 (WGS-84) defined ellipsoid, the difference between the WGS-84 ellipsoidal height and orthometric height represents WGS-84 geoid undulation.

Glide path. A descent profile determined for vertical guidance during a final approach.

Gregorian calendar. Calendar in general use; first introduced in 1582 to define a year that more closely approximates the tropical year than the Julian calendar (ISO 19108*).

Note: In the Gregorian calendar, common years have 365 days and leap years 366 days divided into twelve sequential months.

Height. The vertical distance of a level, a point or an object considered as a point, measured from a specified datum.

Helicopter stand. An aircraft stand which provides for parking a helicopter and where ground taxi operations are completed or where the helicopter touches down and lifts off for air taxi operations.

Heliport. An aerodrome or a defined area on a structure intended to be used wholly or in part for the arrival, departure and surface movement of helicopters.

Heliport reference point (HRP). The designated location of a heliport or a landing location.

Holding procedure. A predetermined manoeuvre which keeps an aircraft within a specified airspace while awaiting further clearance.

Hot spot. A location on an aerodrome movement area with a history or potential risk of collision or runway incursion, and where heightened attention by pilots/drivers is necessary.

Human Factors principles. Principles which apply to aeronautical design, certification, training, operations and maintenance and which seek safe interface between the human and other system components by proper consideration to human performance.

Hypsometric tints. A succession of shades or colour gradations used to depict ranges of elevation.

Initial approach segment. That segment of an instrument approach procedure between the initial approach fix and the intermediate approach fix or, where applicable, the final approach fix or point.

Instrument approach procedure. A series of predetermined manoeuvres by reference to flight instruments with specified protection from obstacles from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, to a position at which holding or en-route obstacle clearance criteria apply.

Integrity classification (aeronautical data). Classification based upon the potential risk resulting from the use of corrupted data. Aeronautical data is classified as:



- (a) routine data: there is a very low probability when using corrupted routine data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe;
- (b) essential data: there is a low probability when using corrupted essential data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe; and
- (c) critical data: there is a high probability when using corrupted critical data that the continued safe flight and landing of an aircraft would be severely at risk with the potential for catastrophe.

Intermediate approach segment. That segment of an instrument approach procedure between either the intermediate approach fix and the final approach fix or point, or between the end of a reversal, racetrack or dead reckoning track procedure and the final approach fix or point, as appropriate.

Intermediate holding position. A designated position intended for traffic control at which taxiing aircraft and vehicles shall stop and hold until further cleared to proceed, when so instructed by the aerodrome control tower.

Isogonal. A line on a map or chart on which all points have the same magnetic variation for a specified epoch.

Isogriv. A line on a map or chart which joins points of equal angular difference between the North of the navigation grid and Magnetic North.

Landing area. That part of a movement area intended for the landing or take-off of aircraft.

Landing direction indicator. A device to indicate visually the direction currently designated for landing and for take-off.

Level. A generic term relating to the vertical position of an aircraft in flight and meaning variously, height, altitude or flight level.

Logon address. A specified code used for data link logon to an ATS unit.

Magnetic variation. The angular difference between True North and Magnetic North.

Note: The value given indicates whether the angular difference is East or West of True North.

Manoeuvring area. That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, excluding aprons.

Marking. A symbol or group of symbols displayed on the surface of the movement area in order to convey aeronautical information.

Metadata. Data about data (ISO 19115*).

Note: Data that describes and documents data.

Minimum en-route altitude (MEA). The altitude for an en-route segment that provides adequate reception of relevant navigation facilities and ATS communications, complies with the airspace structure and provides the required obstacle clearance.



Minimum obstacle clearance altitude (MOCA). The minimum altitude for a defined segment of flight that provides the required obstacle clearance.

Minimum sector altitude (MSA). The lowest altitude which may be used which will provide a minimum clearance of 300 m (1000 ft) above all objects located in an area contained within a sector of a circle of 46 km (25 NM) radius centred on a significant point, the aerodrome reference point (ARP) or the heliport reference point (HRP).

Missed approach point (MAPt). That point in an instrument approach procedure at or before which the prescribed missed approach procedure must be initiated in order to ensure that the minimum obstacle clearance is not infringed.

Missed approach procedure. The procedure to be followed if the approach cannot be continued.

Movement area. That part of an aerodrome to be used for the take-off, landing and taxiing of aircraft, consisting of the manoeuvring area and the apron(s).

Navigation specification. A set of aircraft and flight crew requirements needed to support performance-based navigation operations within a defined airspace. There are two kinds of navigation specifications:

Required navigation performance (RNP) specification. A navigation specification based on area navigation that includes the requirement for performance monitoring and alerting, designated by the prefix RNP, e.g. RNP 4, RNP APCH.

Area navigation (RNAV) specification. A navigation specification based on area navigation that does not include the requirement for performance monitoring and alerting, designated by the prefix RNAV, e.g. RNAV 5, RNAV 1.

Note 1: The Performance-based Navigation (PBN) Manual (Doc 9613), Volume II, contains detailed guidance on navigation specifications.

Note 2: The term RNP, previously defined as “a statement of the navigation performance necessary for operation within a defined airspace”, has been removed from this Annex as the concept of RNP has been overtaken by the concept of PBN. The term RNP in this Annex is now solely used in the context of navigation specifications that require performance monitoring and alerting, e.g. RNP 4 refers to the aircraft and operating requirements, including a 4 NM lateral performance with on-board performance monitoring and alerting that are detailed in Doc 9613.

Obstacle. All fixed (whether temporary or permanent) and mobile objects, or parts thereof, that:

- a) are located on an area intended for the surface movement of aircraft; or
- b) extend above a defined surface intended to protect aircraft in flight; or
- c) stand outside those defined surfaces and that have been assessed as being a hazard to air navigation.

Note: The term obstacle is used in this Annex solely for the purpose of specifying the charting of objects that are considered a potential hazard to the safe passage of aircraft in the type of operation for which the individual chart series is designed.



Obstacle clearance altitude (OCA) or obstacle clearance height (OCH). The lowest altitude or the lowest height above the elevation of the relevant runway threshold or the aerodrome elevation as applicable, used in establishing compliance with appropriate obstacle clearance criteria.

Note 1: Obstacle clearance altitude is referenced to mean sea level and obstacle clearance height is referenced to the threshold elevation or in the case of non-precision approaches to the aerodrome elevation or the threshold elevation if that is more than 2 m (7 ft) below the aerodrome elevation. An obstacle clearance height for a circling approach is referenced to the aerodrome elevation.

Note 2: For convenience when both expressions are used they may be written in the form “obstacle clearance altitude/height” and abbreviated “OCA/H”.

Note 3: See Procedures for Air Navigation Services — Aircraft Operations (Doc 8168), Volume I, Part I, Section 4, Chapter 1, 1.5, and Volume II, Part I, Section 4, Chapter 5, 5.4, for specific applications of this definition.

Obstacle free zone (OFZ). The airspace above the inner approach surface, inner transitional surfaces, and balked landing surface and that portion of the strip bounded by these surfaces, which is not penetrated by any fixed obstacle other than a low-mass and frangibly mounted one required for air navigation purposes.

Orthometric height. Height of a point related to the geoid, generally presented as an MSL elevation.

Performance-based navigation (PBN). Area navigation based on performance requirements for aircraft operating along an ATS route, on an instrument approach procedure or in a designated airspace.

Note: Performance requirements are expressed in navigation specifications (RNAV specification, RNP specification) in terms of accuracy, integrity, continuity, availability and functionality needed for the proposed operation in the context of a particular airspace concept.

Point light. A luminous signal appearing without perceptible length.

Portrayal. Presentation of information to humans (ISO 19117*).

Position (geographical). Set of coordinates (latitude and longitude) referenced to the mathematical reference ellipsoid which define the position of a point on the surface of the Earth.

Precision approach procedure. An instrument approach procedure utilising azimuth and glide path information provided by ILS or PAR.

Procedure altitude/height. A published altitude/height used in defining the vertical profile of a flight procedure, at or above the minimum obstacle clearance altitude/height where established.

Procedure turn. A manoeuvre in which a turn is made away from a designated track followed by a turn in the opposite direction to permit the aircraft to intercept and proceed along the reciprocal of the designated track.

Note 1: Procedure turns are designated “left” or “right” according to the direction of the initial turn.

Note 2: Procedure turns may be designated as being made either in level flight or while descending, according to the circumstances of each individual procedure.

Prohibited area. An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is prohibited.



Relief. The inequalities in elevation of the surface of the Earth represented on aeronautical charts by contours, hypsometric tints, shading or spot elevations.

Reporting point. A specified (named) geographical location in relation to which the position of an aircraft can be reported.

Note: There are three categories of reporting points: ground-based navigation aid, intersection and waypoint. In the context of this definition, intersection is a significant point expressed as radials, bearings and/or distances from ground-based navigation aids. A reporting point can be indicated as “on request” or as “compulsory”.

Restricted area. An airspace of defined dimensions, above the land areas or territorial waters of a State, within which the flight of aircraft is restricted in accordance with certain specified conditions.

Reversal procedure. A procedure designed to enable aircraft to reverse direction during the initial approach segment of an instrument approach procedure. The sequence may include procedure turns or base turns.

Runway. A defined rectangular area on a land aerodrome prepared for the landing and take-off of aircraft.

Runway-holding position. A designated position intended to protect a runway, an obstacle limitation surface, or an ILS/MLS critical/sensitive area at which taxiing aircraft and vehicles shall stop and hold, unless otherwise authorised by the aerodrome control tower.

Note: In radiotelephony phraseologies, the expression “holding point” is used to designate the runway-holding position.

Runway strip. A defined area including the runway and stopway, if provided, intended:

- (a) to reduce the risk of damage to aircraft running off a runway; and
- (b) to protect aircraft flying over it during take-off or landing operations.

Runway visual range (RVR). The range over which the pilot of an aircraft on the centre line of a runway can see the runway surface markings or the lights delineating the runway or identifying its centre line.

Shoulder. An area adjacent to the edge of a pavement so prepared as to provide a transition between the pavement and the adjacent surface.

Significant point. A specified geographical location used in defining an ATS route or the flight path of an aircraft and for other navigation and ATS purposes.

Note: There are three categories of significant points: ground-based navigation aid, intersection and waypoint. In the context of this definition, intersection is a significant point expressed as radials, bearings and/or distances from ground-based navigation aids.

Stopway. A defined rectangular area on the ground at the end of take-off run available prepared as a suitable area in which an aircraft can be stopped in the case of an abandoned take-off.

Taxiing. Movement of an aircraft on the surface of an aerodrome under its own power, excluding take-off and landing.



Taxi-route. A defined path established for the movement of helicopters from one part of a heliport to another. A taxi-route includes a helicopter air or ground taxiway which is centred on the taxi-route.

Taxiway. A defined path on a land aerodrome established for the taxiing of aircraft and intended to provide a link between one part of the aerodrome and another, including:

- (a) **Aircraft stand taxilane.** A portion of an apron designated as a taxiway and intended to provide access to aircraft stands only.
- (b) **Apron taxiway.** A portion of a taxiway system located on an apron and intended to provide a through taxi route across the apron.
- (c) **Rapid exit taxiway.** A taxiway connected to a runway at an acute angle and designed to allow landing aeroplanes to turn off at higher speeds than are achieved on other exit taxiways thereby minimising runway occupancy times.

Terminal arrival altitude (TAA). The lowest altitude that will provide a minimum clearance of 300 m (1000 ft) above all objects located in an arc of a circle defined by a 46 km (25 NM) radius centred on the initial approach fix (IAF), or where there is no IAF on the intermediate approach fix (IF), delimited by straight lines joining the extremity of the arc to the IF. The combined TAAs associated with an approach procedure shall account for an area of 360 degrees around the IF.

Terrain. The surface of the Earth containing naturally occurring features such as mountains, hills, ridges, valleys, bodies of water, permanent ice and snow, and excluding obstacles.

Note: In practical terms, depending on the method of data collection, terrain represents the continuous surface that exists at the bare Earth, the top of the canopy or something in-between, also known as “first reflective surface”.

Threshold. The beginning of that portion of the runway usable for landing.

Touchdown and lift-off area (TLOF). A load bearing area on which a helicopter may touch down or lift off.

Touchdown zone. The portion of a runway, beyond the threshold, where it is intended landing aeroplanes first contact the runway.

Track. The projection on the earth’s surface of the path of an aircraft, the direction of which path at any point is usually expressed in degrees from North (true, magnetic or grid).

Transition altitude. The altitude at or below which the vertical position of an aircraft is controlled by reference to altitudes.

Vectoring. Provision of navigational guidance to aircraft in the form of specific headings, based on the use of an ATS surveillance system.

Visual approach procedure. A series of predetermined manoeuvres by visual reference, from the initial approach fix, or where applicable, from the beginning of a defined arrival route to a point from which a landing can be completed and thereafter, if a landing is not completed, a go-around procedure can be carried out.

Waypoint. A specified geographical location used to define an area navigation route or the flight path of an aircraft employing area navigation. Waypoints are identified as either:



Fly-by waypoint. A waypoint which requires turn anticipation to allow tangential interception of the next segment of a route or procedure; or

Flyover waypoint. A waypoint at which a turn is initiated in order to join the next segment of a route or procedure.

1.2 Applicability

1.2.1 This CAR applies to the provision of all aeronautical charts produced for, on behalf of or by the Authority.

1.2.2 Aeronautical charts service providers shall ensure that all aeronautical charts produced conform to the Standards, Recommended Practices and Specifications contained in ICAO Annex 4 and this regulation

1.3 Availability

1.3.1 *Information.* The Authority shall, on request by another Contracting State provide all information relating to its own territory that is necessary to enable these regulations to be met.

1.3.2 *Charts.* The Authority shall, when so specified, ensure the availability of charts in whichever of the following ways is appropriate for a particular chart or single sheet of a chart series.

Note: The availability of charts includes specified electronic charts.

1.3.2.1 For any chart or single sheet of a chart series entirely contained within the territory of The Bahamas or, having jurisdiction over the territory of another State, the Authority shall either:

- (a) produce a chart or sheet itself; or
- (b) arrange for its production by another Contracting State or by an agency; or
- (c) provide another Contracting State prepared to accept an obligation to produce a chart or sheet with the data necessary for its production

1.3.2.2 For any chart or single sheet of a chart series which includes the territory of two or more Contracting States, the States having jurisdiction over the territory so included shall determine the manner in which a chart or sheet will be made available. This determination shall be made with due regard being given to regional air navigation agreements and to any programme of allocation established by the Council of ICAO.

Note: The phrase “regional air navigation agreements” refers to the agreements approved by the Council of ICAO normally on the advice of regional air navigation meetings.

1.3.3 The Authority shall take all reasonable measures to ensure that information provided for the production of aeronautical charts is adequate and accurate, and that it is maintained and kept up to date by an adequate revision service.

Note: Guidance material on the preparation of aeronautical charts, including sample formats, is contained in the Aeronautical Chart Manual (Doc 8697).



This Page Intentionally Left Blank



CHAPTER 2

GENERAL SPECIFICATIONS

2.1 Operational requirements for charts

Note: For the purposes of this regulation, the following phases of flight are used:

Phase 1 — Taxi from aircraft stand to take-off point

Phase 2 — Take-off and climb to en-route ATS route structure

Phase 3 — En-route ATS route structure

Phase 4 — Descent to approach

Phase 5 — Approach to land and missed approach

Phase 6 — Landing and taxi to aircraft stand.

2.1.1 Each type of chart shall provide information relevant to the function of a chart and its design shall observe Human Factors principles which facilitate its optimum use.

Note: Guidance material on the application of Human Factors principles can be found in the Human Factors Training Manual (Doc 9683).

2.1.2 Each type of chart shall provide information appropriate to the phase of flight to ensure the safe and expeditious operation of the aircraft.

2.1.3 The presentation of information shall be accurate, free from distortion and clutter, unambiguous, and be readable under all normal operating conditions.

2.1.4 Colours or tints and type size used shall be such that a chart can be easily read and interpreted by the pilot in varying conditions of natural and artificial light.

2.1.5 The information shall be in a form which enables the pilot to acquire it in a reasonable time consistent with workload and operating conditions.

2.1.6 The presentation of information provided on each type of chart shall permit smooth transition from chart to chart as appropriate to the phase of flight.

2.1.7 Charts shall be True North orientated.

2.1.8 The basic sheet size of charts shall be 210 x 148 mm (8.27 x 5.82 in) (A5).

2.2 Titles

2.2.1 The title of a chart or chart series prepared in accordance with the specifications contained in ICAO Annex 4, and intended to satisfy the function of a chart, shall be that of the relevant chapter heading, except that titles shall not include "ICAO".



2.3 Miscellaneous information

- 2.3.1 The marginal note layout shall be as given in ICAO Annex 4, Appendix 1, except as otherwise specified for a particular chart.
- 2.3.2 The following information shall be shown on the face of each chart unless otherwise stated in the specification of a chart concerned:
- (a) designation or title of a chart series;
 - (b) name and reference of the sheet;
 - (c) on each margin an indication of the adjoining sheet (when applicable).
- 2.3.3 A legend to the symbols and abbreviations used shall be provided. The legend shall be on the face or reverse of each chart except that, where it is impracticable for reasons of space, a legend may be published separately.
- 2.3.4 The name and adequate address of the producing agency shall be shown in the margin of a chart except that, where a chart is published as part of an aeronautical document, this information may be placed in the front of that document.

2.4 Symbols

- 2.4.1 Symbols used shall conform to those shown in ICAO Annex 4, Appendix 2 — ICAO Chart Symbols, except that where it is desired to show on an aeronautical chart special features or items of importance to civil aviation for which no ICAO symbol is at present provided, any appropriate symbol may be chosen for this purpose, provided that it does not cause confusion with any existing ICAO chart symbol or impair the legibility of a chart.
- 2.4.2 To represent ground-based navigation aids, intersections and waypoints, the same basic symbol shall be used on all charts on which they appear, regardless of chart purpose.
- 2.4.3 The symbol used for significant points shall be based on a hierarchy of symbols and selected in the following order: ground-based navigation aid, intersection, waypoint symbol. A waypoint symbol shall be used only when a particular significant point does not already exist as either a ground-based navigation aid or intersection.
- 2.4.4 Symbols shall be shown in the manner specified in 2.4.2, 2.4.3 and ICAO Annex 4, Appendix 2 — ICAO Chart Symbols, symbol number 121.

2.5 Units of measurement

- 2.5.1 Distances shall be derived as geodesic distances.
- 2.5.2 Distances shall be expressed in either kilometres or nautical miles or both, provided the units are clearly differentiated.
- 2.5.3 Altitudes, elevations and heights shall be expressed in either metres or feet or both, provided the units are clearly differentiated.
- 2.5.4 Linear dimensions on aerodromes and short distances shall be expressed in metres.



- 2.5.5 The order of resolution of distances, dimensions, elevations and heights shall be that as specified for a particular chart.
- 2.5.6 The units of measurement used to express distances, altitudes, elevations and heights shall be conspicuously stated on the face of each chart.
- 2.5.7 Conversion scales (kilometres/nautical miles, metres/feet) shall be provided on each chart on which distances, elevations or altitudes are shown. The conversion scales shall be placed on the face of each chart.

2.6 Scale and projection

- 2.6.1 For charts of large areas, the name and basic parameters and scale of the projection shall be indicated.
- 2.6.2 For charts of small areas, a linear scale only shall be indicated.

2.7 Date of validity of aeronautical information

The date of validity of aeronautical information shall be clearly indicated on the face of each chart.

2.8 Spelling of geographical names

- 2.8.1 The symbols of the Roman alphabet shall be used for all writing.
- 2.8.2 The names of places and of geographical features in countries which officially use varieties of the Roman alphabet shall be accepted in their official spelling, including the accents and diacritical marks used in the respective alphabets.
- 2.8.3 Where a geographical term such as “cape”, “point”, “gulf”, “river” is abbreviated on any particular chart, that word shall be spelt out in full in the language used by the publishing agency, in respect of the most important example of each type. Punctuation marks shall not be used in abbreviations within the body of a chart.

2.9 Abbreviations

- 2.9.1 Abbreviations shall be used on aeronautical charts whenever they are appropriate.
- 2.9.2 Where applicable, abbreviations shall be selected from the Procedures for Air Navigation Services — ICAO Abbreviations and Codes (Doc 8400) or as defined in CAR DEF

2.10 Political boundaries

- 2.10.1 International boundaries shall be shown, but may be interrupted if data more important to the use of a chart would be obscured.
- 2.10.2 Where the territory of more than one State appears on a chart, the names identifying the countries shall be indicated.

2.11 Colours

Colours used on charts shall conform to ICAO Annex 4, Appendix 3 — Colour Guide.



2.12 Relief

2.12.1 Relief, where shown, shall be portrayed in a manner that will satisfy a chart users' need for:

- (a) orientation and identification;
- (b) safe terrain clearance;
- (c) clarity of aeronautical information when shown;
- (d) planning.

Note; Relief is usually portrayed by combinations of contours, hypsometric tints, spot elevations and hill shading, the choice of method being affected by the nature and scale of a chart and its intended use.

2.12.2 Where relief is shown by hypsometric tints, the tints used shall, where possible, be based on those shown in the Hypsometric Tint Guide in ICAO Annex 4, Appendix 4.

2.12.3 Where spot elevations are used, they shall be shown for selected critical points.

2.12.3.1 The value of spot elevations of doubtful accuracy shall be followed by the sign \pm .

2.13 Prohibited, restricted and danger areas

When prohibited, restricted or danger areas are shown, the reference or other identification shall be included, except that the nationality letters may be omitted.

2.14 Air traffic services airspace

2.14.1 When ATS airspace is shown on a chart, the class of airspace, the type, name or call sign, the vertical limits and the radio frequency(ies) to be used shall be indicated and the horizontal limits depicted in accordance with ICAO Annex 4, Appendix 2 — ICAO Chart Symbols.

2.15 Magnetic variation

2.15.1 True North and magnetic variation shall be indicated. The order of resolution of magnetic variation shall be that as specified for a particular chart.

2.15.2 When magnetic variation is shown on a chart, the values shown shall be those for the year nearest to the date of publication that is divisible by 5, i.e. 1980, 1985, etc. However, in exceptional cases where the current value would be more than one degree different, an interim date and value should be quoted.

2.15.3 In large terminal areas with multiple aerodromes, a single rounded value of magnetic variation shall be applied so that the procedures that service multiple aerodromes use a single, common variation value.

2.16 Typography

2.16.1 Typography of a portion of the terrain, where shown, shall be portrayed in a manner that will comply with the technical specifications of the ICAO Aeronautical Chart Manual (Doc 8697).



2.17 Aeronautical data

- 2.17.1 All necessary measures shall be taken to introduce a properly organised quality system containing procedures, processes and resources necessary to implement quality management at each function stage. The execution of such quality management shall be made demonstrable for each function stage, when required. In addition, procedures shall be established in order to ensure that aeronautical data at any moment is traceable to its origin so as to allow any data anomalies or errors, detected during the production/maintenance phases or in the operational use, to be corrected.
- 2.17.2 Chart resolution of aeronautical data shall be that as specified for a particular chart.
- 2.17.3 The integrity of aeronautical data shall be maintained throughout the data process from origination to distribution to the next intended user.
- 2.17.4 Digital data error detection techniques shall be used during the transmission and/or storage of aeronautical data and digital data sets.

2.18 Common reference systems

2.18.1 Horizontal reference system

- 2.18.1.1 World Geodetic System — 1984 (WGS-84) shall be used as the horizontal (geodetic) reference system. Published aeronautical geographical coordinates (indicating latitude and longitude) shall be expressed in terms of the WGS-84 geodetic reference datum.
- 2.18.1.2 Geographical coordinates which have been transformed into WGS-84 coordinates but whose accuracy of original field work does not meet the required internationally recognised standards, shall be identified by an asterisk.
- 2.18.1.3 Chart resolution of geographical coordinates shall be that specified for a particular chart series.

2.18.2 Vertical reference system

- 2.18.2.1 Mean sea level (MSL) datum, which gives the relationship of gravity-related height (elevation) to a surface known as the geoid, shall be used as the vertical reference system.
- 2.18.2.2 In addition to the elevations referenced to MSL, for the specific surveyed ground positions, geoid undulation (referenced to the WGS-84 ellipsoid) for those positions shall also be published as specified for a particular chart.
- 2.18.2.3 Chart resolution of elevation and geoid undulation shall be that specified for a particular chart series.

2.18.3 Temporal reference system

- 2.18.3.1 The Gregorian calendar and Coordinated Universal Time (UTC) shall be used as the temporal reference system.
- 2.18.3.2 When a different temporal reference system is used for charting, this shall be indicated in GEN 2.1.2 of the Aeronautical Information Publication (AIP).



This Page Intentionally Left Blank



CHAPTER 3

AERODROME OBSTACLE CHART — ICAO TYPE A (OPERATING LIMITATIONS)

3.1 Function

This chart, in combination with the relevant information published in the AIP, shall provide the data necessary to enable an operator to comply with fixed-wing and rotary aircraft performance operating limitations.

3.2 Availability

3.2.1 Aerodrome Obstacle Charts — ICAO Type A (Operating Limitations) shall be made available in the manner prescribed in 1.3.2 for all aerodromes regularly used by international civil aviation, except for those aerodromes where there are no obstacles in the take-off flight path areas or where the Aerodrome Terrain and Obstacle Chart — ICAO (Electronic) is provided in accordance with Chapter 5.

3.2.2 Where a chart is not required because no obstacles exist in the take-off flight path area, a notification to this effect shall be published in the AIP.

3.3 Units of measurement

3.3.1 Elevations shall be shown to the nearest half-metre or to the nearest foot.

3.3.2 Linear dimensions shall be shown to the nearest half-metre.

3.4 Coverage and scale

3.4.1 The extent of each plan shall be sufficient to cover all obstacles except, where an isolated distant obstacle unnecessarily increases a sheet size. In these instances, an arrow shall be used along with the appropriate symbol, along with details of the of the distance, bearing and elevation of the obstacle from the end of the applicable runway

3.4.2 The horizontal scale shall be within the range of 1:10000 to 1:15000.

3.4.3 The vertical scale shall be ten times the horizontal scale.

3.4.4 Horizontal and vertical linear scales showing both metres and feet shall be included in charts.

3.5 Format

3.5.1 Charts shall depict a plan and profile of each runway, any associated stopway or clearway, the take-off flight path area and obstacles.

3.5.2 The profile for each runway, stopway, clearway and the obstacles in the take-off flight path area shall be shown above its corresponding plan. The profile of an alternative take-off flight path area shall comprise a linear projection of the full take-off flight path and shall be disposed above its corresponding plan in the manner most suited to the ready interpretation of the information.



3.5.3 A profile grid shall be ruled over the entire profile area exclusive of the runway. The zero for vertical coordinates shall be mean sea level. The zero for horizontal coordinates shall be the end of the runway furthest from the take-off flight path area concerned. Graduation marks indicating the sub-divisions of intervals shall be shown along the base of the grid and along the vertical margins.

3.5.4 A chart shall include:

- (a) a box for recording the operational data specified in 3.8.3;
- (b) a box for recording amendments and dates thereof.

3.6 Identification

A chart shall be identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the designator(s) of the runway(s).

3.7 Magnetic variation

The magnetic variation to the nearest degree and date of information shall be indicated.

3.8 Aeronautical data

3.8.1 Obstacles

3.8.1.1 Objects in the take-off flight path area which project above a plane surface having a 1.2 per cent slope and having a common origin with the take-off flight path area shall be regarded as obstacles, except that obstacles lying wholly below the shadow of other obstacles as defined in 3.8.1.2 need not be shown. Mobile objects such as boats, trains and trucks, which may project above the 1.2 per cent plane, shall be considered obstacles but shall not be considered as being capable of creating a shadow.

3.8.1.2 The shadow of an obstacle is considered to be a plane surface originating at a horizontal line passing through the top of the obstacle at right angles to the centre line of the take-off flight path area. The plane covers the complete width of the take-off flight path area and extends to the plane defined in 3.8.1.1 or to the next higher obstacle if it occurs first. For the first 300 m (1000 ft) of the take-off flight path area, the shadow planes are horizontal and beyond this point such planes have an upward slope of 1.2 per cent.

3.8.1.3 If the obstacle creating a shadow is likely to be removed, objects that would become obstacles by its removal shall be shown.

3.8.2 Take-off flight path area

3.8.2.1 The take-off flight path area consists of a quadrilateral area on the surface of the earth lying directly below, and symmetrically disposed about, the take-off flight path. This area has the following characteristics:

- (a) it commences at the end of the area declared suitable for take-off (i.e. at the end of the runway or clearway as appropriate);



- (b) its width at the point of origin is 180 m (600 ft) and this width increases at the rate of 0.25D to a maximum of 1 800 m (6000 ft), where D is the distance from the point of origin;
- (c) it extends to the point beyond which no obstacles exist or to a distance of 10.0 km (5.4 NM), whichever is the lesser.

3.8.2.2 For runways serving aircraft having operating limitations which do not preclude the use of a take-off flight path gradient of less than 1.2 per cent, the extent of the take-off flight path area specified in 3.8.2.1 c) shall be increased to not less than 12.0 km (6.5 NM) and the slope of the plane surface specified in 3.8.1.1 and 3.8.1.2 shall be reduced to 1.0 per cent or less.

3.8.3 Declared distances

3.8.3.1 The following information for each direction of each runway shall be entered in the space provided:

- (a) take-off run available;
- (b) accelerate-stop distance available;
- (c) take-off distance available;
- (d) landing distance available.

3.8.3.2 Where a declared distance is not provided because a runway is usable in one direction only, that runway shall be identified as “not usable for take-off, landing or both”.

3.8.4 Plan and profile views

3.8.4.1 The plan view shall show:

- (a) the outline of the runways by a solid line, including the length and width, the magnetic bearing to the nearest degree, and the runway number;
- (b) the outline of the clearways by a broken line, including the length and identification as such;
- (c) take-off flight path areas by a dashed line and the centre line by a fine line consisting of short and long dashes;
- (d) alternative take-off flight path areas. When alternative take-off flight path areas not centred on the extension of the runway centre line are shown, notes shall be provided explaining the significance of such areas;
- (e) obstacles, including:
 - (1) the exact location of each obstacle together with a symbol indicative of its type;
 - (2) the elevation and identification of each obstacle;
 - (3) the limits of penetration of obstacles of large extent in a distinctive manner identified in the legend.



Note: This does not exclude the necessity for indicating critical spot elevations within the take-off flight path area.

3.8.4.1.1 The nature of the runway and stopway surfaces shall be indicated.

3.8.4.1.2 Stopways should be identified as such and shall be shown by a broken line.

3.8.4.1.3 When stopways are shown, the length of each stopway shall be indicated.

3.8.4.2 The profile view shall show:

- (a) the profile of the centre line of the runway by a solid line and the profile of the centre line of any associated stopways and clearways by a broken line;
- (b) the elevation of the runway centre line at each end of the runway, at the stopway and at the origin of each take-off flight path area, and at each significant change in slope of runway and stopway;
- (c) obstacles, including:
 - (1) each obstacle by a solid vertical line extending from a convenient grid line over at least one other grid line to the elevation of the top of the obstacle;
 - (2) identification of each obstacle;
 - (3) the limits of penetration of obstacles of large extent in a distinctive manner identified in the legend.

3.9 Accuracy

3.9.1 The order of accuracy attained shall be shown on a chart.

3.9.2 *Datum.* Where no accurate datum for vertical reference is available, the elevation of the datum used shall be stated and shall be identified as assumed.



CHAPTER 4

AERODROME OBSTACLE CHART — ICAO TYPE B

4.1 Function

4.1.1 This chart shall provide information to satisfy the following functions:

- (a) the determination of minimum safe altitudes/heights including those for circling procedures;
- (b) the determination of procedures for use in the event of an emergency during take-off or landing;
- (c) the application of obstacle clearing and marking criteria; and
- (d) the provision of source material for aeronautical charts.

4.2 Availability

4.2.1 When produced, aerodrome obstacle charts — ICAO Type B are to be made available, in the manner prescribed in 1.3.2, for all aerodromes regularly used by international civil aviation except for those aerodromes where the Aerodrome Terrain and Obstacle Chart — ICAO (Electronic) is provided in accordance with Chapter 5.

4.2.2 When a chart combining the specifications of Chapters 3 and 4 is made available, it shall be called the Aerodrome Obstacle Chart — ICAO (Comprehensive).

4.3 Units of measurement

4.3.1 Elevations shall be shown to the nearest half-metre or to the nearest foot.

4.3.2 Linear dimensions shall be shown to the nearest half-metre.

4.4 Coverage and scale

The extent of each plan shall be sufficient to cover all obstacles, except when an isolated distant obstacle unnecessarily increases a sheet size, this may be indicated by the appropriate symbol and an arrow, provided that the distance and bearing from the aerodrome reference point and elevation are given.

4.4.1 The horizontal scale shall be within the range of 1:10000 to 1:20000.

4.4.2 A horizontal linear scale showing both metres and feet shall be included in a chart. When necessary, a linear scale for kilometres and a linear scale for nautical miles shall also be shown.

4.5 Format

Charts shall include:

- (a) any necessary explanation of the projection used;
- (b) any necessary identification of the grid used;



- (c) a notation indicating that obstacles are those which penetrate the surfaces specified in CAR AGA Part 1
- (d) a box for recording amendments and dates thereof; and
- (e) outside the neat line, every minute of latitude and longitude marked in degrees and minutes.

4.6 Identification

Charts shall be identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, and the name of the aerodrome.

4.7 Culture and topography

- 4.7.1 Drainage and hydrographic details shall be kept to a minimum.
- 4.7.2 Buildings and other salient features associated with the aerodrome shall be shown. Wherever possible, they shall be shown to scale.
- 4.7.3 All objects, either cultural or natural, that project above the take-off and approach surfaces specified in 4.9 or the clearing and marking surfaces specified in CAR AGA Part 1 shall be shown.
- 4.7.4 Roads and railroads within the take-off and approach area, and less than 600 m (2000 ft) from the end of the runway or runway extensions, shall be shown.

4.8 Magnetic variation

A chart shall show a compass rose orientated to the True North, or a North point, showing the magnetic variation to the nearest degree with the date of magnetic information and annual change.

4.9 Aeronautical data

- 4.9.1 Charts shall show:
 - (a) the aerodrome reference point and its geographical coordinates in degrees, minutes and seconds;
 - (b) the outline of the runways by a solid line;
 - (c) the length and width of the runway;
 - (d) the magnetic bearing to the nearest degree of the runway and the runway number;
 - (e) the elevation of the runway centre line at each end of the runway, at the stopway, at the origin of each take-off and approach area, and at each significant change of slope of runway and stopway;
 - (f) taxiways, aprons and parking areas identified as such, and the outlines by a solid line;
 - (g) stopways identified as such and depicted by a broken line;



- (h) the length of each stopway;
- (i) clearways identified as such and depicted by a broken line;
- (j) the length of each clearway;
- (k) take-off and approach surfaces identified as such and depicted by a broken line;
- (l) take-off and approach areas;
- (m) obstacles at their exact location, including:
 - (1) a symbol indicative of their type;
 - (2) elevation;
 - (3) identification;
 - (4) limits of penetration of large extent in a distinctive manner identified in the legend;
- (n) any additional obstacles, as determined by 3.8.1.1 including the obstacles in the shadow of an obstacle, which would otherwise be exempted.

4.9.1.1 The nature of the runway and stopway surfaces shall be given.

4.9.1.2 Wherever practicable, the highest object or obstacle between adjacent approach areas within a radius of 5000 m (15000 ft) from the aerodrome reference point shall be indicated in a prominent manner.

4.9.1.3 The extent of tree areas and relief features, part of which constitute obstacles, shall be shown.

4.10 Accuracy

4.10.1 The order of accuracy attained shall be shown on a chart.

4.10.2 The order of accuracy of the field work and the precision of chart production shall be within the maximum deviations indicated herein:

- (a) Take-off and approach areas:
 - (1) horizontal distances: 5 m (15 ft) at point of origin increasing at a rate of 1 per 500;
 - (2) vertical distances: 0.5 m (1.5 ft) in the first 300 m (1000 ft) and increasing at a rate of 1 per 1000.
- (b) Other areas:
 - (1) horizontal distances: 5 m (15 ft) within 5000 m (15000 ft) of the aerodrome reference point and 12 m (40 ft) beyond that area;
 - (2) vertical distances: 1 m (3 ft) within 1 500 m (5000 ft) of the aerodrome reference point increasing at a rate of 1 per 1000.



4.10.3 *Datum*. Where no accurate datum for vertical reference is available, the elevation of the datum used shall be stated and identified as assumed.



CHAPTER 5

AERODROME TERRAIN AND OBSTACLE CHART — ICAO (ELECTRONIC)

5.1 Function

- 5.1.1 This electronic chart shall portray the terrain and obstacle data in combination with aeronautical data, as appropriate, necessary to:
- (a) enable an operator to comply with fixed-wing and rotary aircraft operating limitations, by developing contingency procedures for use in the event of an emergency during a missed approach or take-off, and by performing aircraft operating limitations analysis; and
 - (b) support the following air navigation applications:
 - (1) instrument procedure design (including circling procedure);
 - (2) aerodrome obstacle restriction and removal; and
 - (3) provision of source data for the production of other aeronautical charts.

5.2 Availability

- 5.2.1 Aerodrome Terrain and Obstacle Charts — ICAO (Electronic) shall be made available in the manner prescribed in 1.3.2 for aerodromes regularly used by international civil aviation.

Note: Where the Aerodrome Terrain and Obstacle Chart — ICAO (Electronic) is made available, the Aerodrome Obstacle Chart — ICAO Type A (Operating Limitations) and the Aerodrome Obstacle Chart — ICAO Type B are not required (see 3.2.1 and 4.2.1).

- 5.2.2 Aerodrome Terrain and Obstacle Charts — ICAO (Electronic) shall be made available in the manner prescribed in 1.3.2 for all aerodromes regularly used by international civil aviation.
- 5.2.3 The Aerodrome Terrain and Obstacle Chart — ICAO (Electronic) shall also be made available in hard copy format upon request.
- 5.2.4 The ISO 19100 series of standards for geographic information shall be used as a general data modelling framework.

5.3 Identification

Electronic charts shall be identified by the name of the country in which the aerodrome is located, the name of the city or town which the aerodrome serves, and the name of the aerodrome.

5.4 Chart coverage

- 5.4.1 The chart shall be sufficient to cover the vicinity of an aerodrome sub-divided as follows:
- (a) a rectangular area around a runway that comprises the runway strip plus any clearway that exists;
 - (b) an area extending from the ends of the area in (a) in the direction of departure with a length of 10 km and a splay of 15 percent to each side;



- (c) an area outside those specified in (a) and (b) at a distance of not more than 10km of the boundary of that described in (a); and
- (d) an area outside of that described in (a), (b) and (c) up to a distance of 45 km from the aerodrome reference point, or to an existing terminal control area (TMA) boundary, whichever is the nearest.

5.5 Chart content

5.5.1 General

5.5.1.1 When developing computer graphic applications that are used to portray features on a chart, the relationships between features, feature attributes, and the underlying spatial geometry and associated topological relationships shall be specified by an application schema. Portrayed information shall be provided on the basis of portrayal specifications applied according to defined portrayal rules. Portrayal specifications and portrayal rules shall not be part of the data set. Portrayal rules shall be stored in a portrayal catalogue which shall make reference to separately stored portrayal specifications.

5.5.1.2 Symbols used to portray features shall be in accordance with 2.4 and ICAO Annex 4, Appendix 2 — ICAO Chart Symbols.

5.5.2 Terrain feature

5.5.2.1 The terrain feature, and associated attributes, to be portrayed and database-linked to a chart, shall be based on the terrain data sets within the vicinity of an aerodrome as follows;

- (a) a rectangular area around a runway that comprises the runway strip plus any clearway that exists;
- (b) an area extending from the ends of that specified in (1) in the direction of departure, with a length of 10 km and a splay of 15 per cent to each side;
- (c) an area extending outside those specified in (1) and (2) at a distance of not more than 10 km from the boundary of that specified in (1); and
- (d) an area outside those specified in (1), (2) and (3) up to a distance of 45 km from the aerodrome reference point, or to an existing terminal control area (TMA) boundary, whichever is nearest;
- (e) the area bordering an aerodrome movement area that extends horizontally from the edge of a runway to 90 m from the runway centre line and 50 m from the edge of all other parts of the aerodrome movement area; and
- (f) the area extending 900 m prior to the runway threshold and 60 m each side of the extended runway centre line in the direction of the approach on a precision approach runway, Category II or III.

5.5.2.2 The terrain feature shall be portrayed in a manner that provides an effective general impression of a terrain. This shall be a representation of terrain surface by continuous elevation values at all intersections of the defined grid, also known as the Digital Elevation Model (DEM).



5.5.2.3 Representation of terrain surface shall be provided as a selectable layer of contour lines in addition to the DEM.

5.5.2.4 Portrayed terrain features shall be linked to the following associated attributes in a database(s):

- (a) horizontal positions of grid points in geographic coordinates and elevations of the points;
- (b) surface type;
- (c) contour line values, if provided; and
- (d) names of cities, towns and other prominent topographic features.

5.5.3 Obstacle features

5.5.3.1 Obstacle features, and associated attributes, portrayed or database-linked to a chart shall be based on obstacle data sets which satisfy the requirements of this regulation.

5.5.3.2 Each obstacle shall be portrayed by an appropriate symbol and obstacle identifier.

5.5.3.3 The portrayed obstacle feature shall be linked to the following associated attributes in the database(s):

- (a) horizontal position in geographic coordinates and associated elevation;
- (b) obstacle type; and
- (c) obstacle extent, if appropriate.

5.5.4 Aerodrome features

5.5.4.1 Aerodrome features, and associated attributes, portrayed and database-linked to a chart shall be based on aerodrome data which satisfy the requirements of ICAO Annex 15, Chapter 5.

5.5.4.2 The following aerodrome features shall be portrayed by an appropriate symbol:

- (a) aerodrome reference point;
- (b) runway(s), with designation numbers, and if available, stopway(s) and clearway(s); and
- (c) taxiways, aprons, large buildings and other prominent aerodrome features.

5.5.4.3 The portrayed aerodrome feature shall be linked to the following associated attributes in the database(s):

- (a) geographical coordinates of the aerodrome reference point;
- (b) aerodrome magnetic variation, year of information and annual change;
- (c) length and width of runway(s), stopway(s) and clearway(s);
- (d) type of surface of runway(s) and stopway(s);



- (e) magnetic bearings of the runway(s) to the nearest degree;
- (f) elevations at each end of runway(s), stopway(s) and clearway(s), and at each significant change in slope of runway(s) and stopway(s);
- (g) declared distances for each runway direction, or the abbreviation “NU”, where a runway direction cannot be used for take-off or landing or both.

5.5.5 Radio navigation aid features

Each radio navigation aid feature located within a chart coverage shall be portrayed by an appropriate symbol.

5.6 Accuracy and resolution

- 5.6.1 The order of accuracy of aeronautical, terrain and obstacle data shall be in accordance with its intended use.
- 5.6.2 The aeronautical, terrain and obstacle data resolution shall be commensurate with the actual data accuracy.

5.7 Electronic functionality

- 5.7.1 It shall be possible to vary the scale at which a chart is viewed. Symbols and text size shall vary with chart scale to enhance readability.
- 5.7.2 Information on charts shall be geo-referenced, and it shall be possible to determine cursor position to at least the nearest second.
- 5.7.3 Charts shall be compatible with widely available desktop computer hardware, software and media.
- 5.7.4 When produced in a form that is not widely available, charts shall include an appropriate software reader.
- 5.7.5 It shall not be possible to remove information from a chart without an authorised update.
- 5.7.6 When, due to congestion of information, the details necessary to support the function of a chart cannot be shown with sufficient clarity on a single comprehensive chart view, selectable information layers shall be provided to allow for the customised combination of information.
- 5.7.7 It shall be possible to print a chart in hard copy format according to the content specifications and scale determined by the user.

5.8 Chart data product specifications

- 5.8.1 A comprehensive statement of data sets shall be provided in the form of data product specifications on which basis air navigation users will be able to evaluate chart data product and determine whether it fulfils the requirements for its intended use (application).
- 5.8.2 Chart data product specifications shall include an overview, a specification scope, a data product identification, data content information, the reference systems used, the data quality requirements, and information on data capture, data maintenance, data portrayal, data product delivery, as well as any additional information available, and metadata.



- 5.8.3 The overview of chart data product specifications shall provide an informal description of the product and shall contain general information about the data product. The specification scope of chart data product specifications shall contain the spatial (horizontal) extent of chart coverage. Chart data product identification shall include the title of the product, a brief narrative summary of the content and purpose, and a description of the geographic area covered by a chart.
- 5.8.4 The data content of chart data product specifications shall clearly identify the type of coverage and/or imagery and shall provide a narrative description of each.
- 5.8.5 Chart data product specifications shall include information that defines the reference systems used. This shall include the spatial reference system (horizontal and vertical) and, if appropriate, temporal reference system. Chart data product specifications shall identify the data quality requirements. This shall include a statement on acceptable conformance quality levels and corresponding data quality measures. This statement shall cover all the data quality elements and data quality sub-elements, even if only to state that a specific data quality element or sub-element is not applicable.
- 5.8.6 Chart data product specifications shall include a data capture statement which shall be a general description of the sources and of processes applied for the capture of chart data. The principles and criteria applied in the maintenance of a chart shall also be provided in chart data product specifications, including the frequency with which a chart product is updated. Of particular importance shall be the maintenance information of obstacle data sets included on a chart and an indication of the principles, methods and criteria applied for obstacle data maintenance.
- 5.8.7 Chart data product specifications shall contain information on how data are portrayed on a chart, as detailed in 5.5.1.1. Chart data product specifications shall also contain data product delivery information which shall include delivery formats and delivery medium information.
- 5.8.8 Core chart metadata elements shall be included in chart data product specifications. Any additional metadata items required to be supplied shall be stated in the product specifications together with the format and encoding of the metadata.



This Page Intentionally Left Blank



CHAPTER 6

PRECISION APPROACH TERRAIN CHART — ICAO

6.1 Function

A chart shall provide detailed terrain profile information within a defined portion of the final approach so as to enable aircraft operating agencies to assess the effect of the terrain on decision height determination by the use of radio altimeters.

6.2 Availability

6.2.1 The Precision Approach Terrain Chart — ICAO shall be made available for all precision approach runways Categories II and III at aerodromes used by international civil aviation, except where the requisite information is provided in the Aerodrome Terrain and Obstacle Chart — ICAO (Electronic) in accordance with Chapter 5.

6.2.2 The Precision Approach Terrain Chart — ICAO shall be revised whenever any significant change occurs.

6.3 Scale

6.3.1 The horizontal scale shall be 1:2500, and the vertical scale 1:500.

6.3.2 When a chart includes a profile of the terrain to a distance greater than 900 m (3000 ft) from the runway threshold, the horizontal scale shall be 1:5000.

6.4 Identification

A chart shall be identified by the name of the country in which the aerodrome is located, the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the designator of the runway.

6.5 Plan and profile information

6.5.1 A chart shall include:

- (a) a plan showing contours at 1 m (3 ft) intervals in the area 60 m (200 ft) on either side of the extended centre line of the runway, to the same distance as the profile, the contours to be related to the runway threshold;
- (b) an indication where the terrain or any object thereon, within the plan defined in a), differs by ≥ 3 m (10 ft) in height from the centre line profile and is likely to affect a radio altimeter;
- (c) a profile of the terrain to a distance of 900 m (3000 ft) from the threshold along the extended centre line of the runway.

6.5.2 ILS reference datum heights shall be shown to the nearest half metre or foot.



This Page Intentionally Left Blank

**CHAPTER 7****ENROUTE CHART — ICAO****7.1 Function**

This chart shall provide flight crews with information to facilitate navigation along ATS routes in compliance with air traffic services procedures.

7.2 Availability

7.2.1 The Enroute Chart — ICAO shall be made available in the manner prescribed in 1.3.2 for all areas where flight information regions have been established.

7.2.2 Where different air traffic services routes, position reporting requirements or lateral limits of flight information regions or control areas exist in different layers of airspace and cannot be shown with sufficient clarity on one chart, separate charts shall be provided.

7.3 Coverage and scale

Note: A uniform scale for charts of this type cannot be specified due to the varying degree of congestion of information in certain areas.

7.3.1 Large variations of scale between adjacent charts showing a continuous route structure shall be avoided.

7.3.2 An adequate overlap of charts shall be provided to ensure continuity of navigation.

7.4 Projection

7.4.1 A conformal projection on which a straight line approximates a great circle shall be used.

7.4.2 Parallels and meridians shall be shown at suitable intervals.

7.4.3 Graduation marks shall be placed at consistent intervals along selected parallels and meridians.

7.5 Identification

Each sheet shall be identified by a chart series and number.

7.6 Culture and topography

7.6.1 Generalised shore lines of all open water areas, large lakes and rivers shall be shown except where they conflict with data more applicable to the function of a chart.

7.6.2 Within each quadrilateral formed by the parallels and meridians, the area minimum altitude shall be shown, except as provided for in 7.6.3.

7.6.3 In areas of high latitude where it is determined by the appropriate authority that True North orientation of a chart is impractical, the area minimum altitude shall be shown within each quadrilateral formed by reference lines of the graticule (grid) used.



7.6.4 Where charts are not True North orientated, this fact and the selected orientation used shall be clearly indicated.

7.7 Magnetic variation

Isogonals shall be indicated and the date of the isogonic information given.

7.8 Bearings, tracks and radials

7.8.1 Bearings, tracks and radials shall be magnetic, except as provided for in 7.8.2. Where bearings and tracks are additionally provided as true values for RNAV segments, they shall be shown in parentheses to the nearest tenth of a degree, e.g. 290° (294.9°T).

7.8.2 In areas of high latitude where it is determined by the appropriate authority that reference to Magnetic North is impractical, another suitable reference, i.e. True North or Grid North, shall be used.

7.8.3 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

7.9 Aeronautical data

7.9.1 Aerodromes

All aerodromes used by international civil aviation to which an instrument approach can be made shall be shown.

7.9.2 Prohibited, restricted and danger areas

Prohibited, restricted and danger areas relevant to the layer of airspace shall be depicted with their identification and vertical limits.

7.9.3 Air traffic services system

7.9.3.1 Where appropriate, the components of the established air traffic services system shall be shown.

7.9.3.1.1 The components shall include the following:

- (a) the radio navigation aids associated with the air traffic services system together with their names, identifications, frequencies and geographical coordinates in degrees, minutes and seconds;
- (b) in respect of DME, additionally the elevation of the transmitting antenna of the DME to the nearest 30 m (100 ft);
- (c) an indication of all designated airspace, including lateral and vertical limits and the appropriate class of airspace;
- (d) All ATS routes for en-route flight including route designators, the track to the nearest degree in both directions along each segment of the routes and, where established, the designation of the navigation specification(s) including any limitations and the direction of traffic flow;



- (e) all significant points which define the ATS routes and are not marked by the position of a radio navigation aid, together with their name-codes and geographical coordinates in degrees, minutes and seconds;
- (f) in respect of waypoints defining VOR/DME area navigation routes, additionally,
 - (1) the station identification and radio frequency of the reference VOR/DME;
 - (2) the bearing to the nearest tenth of a degree and the distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference VOR/ DME, if the waypoint is not co-located with it;
- (g) an indication of all compulsory and “on-request” reporting points and ATS/MET reporting points;
- (h) the distances to the nearest kilometre or nautical mile between significant points constituting turning points or reporting points;
- (i) change-over points on route segments defined by reference to very high frequency omnidirectional radio ranges, indicating the distances to the nearest kilometre or nautical mile to the navigation aids;
- (j) minimum en-route altitudes and minimum obstacle clearance altitudes, on ATS routes to the nearest higher 50 metres or 100 feet (see Annex 11, 2.22);
- (k) communication facilities listed with their channels and, if applicable, logon address and satellite voice communications (SATVOICE) number; and
- (l) air defence identification zone (ADIZ) properly identified.

7.9.4 Supplementary information

7.9.4.1 Details of departure and arrival routes and associated holding patterns in terminal areas shall be shown unless they are shown on an Area Chart, a Standard Departure Chart — Instrument (SID) — ICAO or a Standard Arrival Chart — Instrument (STAR) — ICAO.

7.9.4.2 Where established, altimeter setting regions shall be shown and identified.



This Page Intentionally Left Blank



CHAPTER 8

AREA CHART — ICAO

8.1 Function

8.1.1 This chart shall provide the flight crew with information to facilitate the following phases of instrument flight:

- (a) the transition between the en-route phase and approach to an aerodrome;
- (b) the transition between take-off/missed approach and en-route phase of flight; and
- (c) flights through areas of complex ATS routes or airspace structure.

8.2 Availability

8.2.1 The Area Chart — ICAO shall be made available in the manner prescribed in 1.3.2 where the air traffic services routes or position reporting requirements are complex and cannot be adequately shown on an Enroute Chart — ICAO.

8.2.2 Where air traffic services routes or position reporting requirements are different for arrivals and for departures, and these cannot be shown with sufficient clarity on one chart, separate charts shall be provided.

Note: Under certain conditions, a Standard Departure Chart — Instrument (SID) — ICAO and a Standard Arrival Chart Instrument (STAR) — ICAO may have to be provided (see Chapters 9 and 10).

8.3 Coverage and scale

8.3.1 Chart coverage shall extend to points that effectively show departure and arrival routes.

8.3.2 A chart shall be drawn to scale and a scale-bar shown.

8.4 Projection

8.4.1 Parallels and meridians shall be shown at suitable intervals.

8.4.2 Graduation marks shall be placed at consistent intervals along the neat lines, as appropriate.

8.5 Identification

A chart shall be identified by a name associated with the airspace portrayed.

8.6 Culture and topography

8.6.1 Generalised shorelines of all open water areas, large lakes and rivers shall be shown except where they conflict with data more applicable to the function of a chart.

8.7 Magnetic variation

The average magnetic variation of the area covered by a chart shall be shown to the nearest degree.



8.8 Bearings, tracks and radials

- 8.8.1 Bearings, tracks and radials shall be magnetic, except as provided for in 8.8.2. Where bearings and tracks are additionally provided as true values for RNAV segments, they shall be shown in parentheses to the nearest tenth of a degree, e.g. 290° (294.9°T).
- 8.8.2 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

8.9 Aeronautical data

8.9.1 Aerodromes

All aerodromes which affect the terminal routings shall be shown. Where appropriate, a runway pattern symbol shall be used.

8.9.2 Prohibited, restricted and danger areas

Prohibited, restricted and danger areas shall be depicted with their identification and vertical limits.

8.9.3 Area minimum altitudes

Area minimum altitudes shall be shown within quadrilaterals formed by the parallels and meridians.

8.9.4 Air traffic services system

8.9.4.1 The components of the established relevant air traffic services system shall be shown.

8.9.4.1.1 The components shall include the following:

- (a) the radio navigation aids associated with the air traffic services system, together with their names, identifications, frequencies and geographical coordinates in degrees, minutes and seconds;
- (b) in respect of DME, additionally the elevation of the transmitting antenna of the DME to the nearest 30 m (100 ft);
- (c) terminal radio aids which are required for outbound and inbound traffic and for holding patterns;
- (d) the lateral and vertical limits of all designated airspace and the appropriate class of airspace;
- (e) the designation of the navigation specification(s) including any limitations, where established;
- (f) holding patterns and terminal routings, together with the route designators, and the track to the nearest degree along each segment of the prescribed airways and terminal routings;
- (g) all significant points which define the terminal routings and are not marked by the position of a radio navigation aid, together with their name-codes and geographical coordinates in degrees, minutes and seconds;



- (h) in respect of waypoints defining VOR/DME area navigation routes, additionally,
 - (1) the station identification and radio frequency of the reference VOR/DME;
 - (2) the bearing to the nearest tenth of a degree and the distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference VOR/DME, if the waypoint is not collocated with it;
- (i) an indication of all compulsory and “on-request” reporting points;
- (j) the distances to the nearest kilometre or nautical mile between significant points constituting turning points or reporting points;
- (k) change-over points on route segments defined by reference to very high frequency omnidirectional radio ranges, indicating the distances to the nearest kilometre or nautical mile to the radio navigation aids;

Note: Change-over points established at midpoint between two aids, or at the intersection of two radials in the case of a route which changes direction between the aids, need not be shown for each route segment if a general statement regarding their existence is made.

- (l) minimum en-route altitudes and minimum obstacle clearance altitudes, on ATS routes to the nearest higher 50 metres or 100 feet (see Annex 11, 2.22);
- (m) established minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;

Note 1: Where ATS surveillance systems are used to vector aircraft to or from significant points on a published standard departure or arrival route or to issue clearance for descent below the minimum sector altitude during arrival, the relevant procedures is to be shown on the Area Chart — ICAO unless excessive chart clutter will result.

Note 2: Where excessive chart clutter will result, an ATC Surveillance Minimum Altitude Chart — ICAO is to be provided (see Chapter 21), in which case the elements indicated by 8.9.4.1.1, l), need not be duplicated on the Area Chart — ICAO.

- (n) area speed and level/altitude restrictions where established;
- (o) communication facilities listed with their channels and, if applicable, logon address and SATVOICE number; and
- (p) an indication of “flyover” significant points.



This Page Intentionally Left Blank



CHAPTER 9

STANDARD DEPARTURE CHART — INSTRUMENT (SID) — ICAO

9.1 Function

This chart shall provide the flight crew with information to enable it to comply with the designated standard departure route — instrument from take-off phase to the en-route phase.

9.2 Availability

The Standard Departure Chart — Instrument (SID) — ICAO shall be made available wherever a standard departure route — instrument has been established and cannot be shown with sufficient clarity on the Area Chart — ICAO.

9.3 Coverage and scale

9.3.1 Chart coverage shall be sufficient to indicate the point where a departure route begins and the specified significant point at which the en-route phase of flight along a designated air traffic services route can be commenced.

Note: The departure route normally originates at the end of a runway.

9.3.2 If a chart is drawn to scale, a scale-bar shall be shown.

9.3.3 When a chart is not drawn to scale, the annotation “NOT TO SCALE” shall be shown and the symbol for scale- break shall be used on tracks and other aspects of a chart which are too large to be drawn to scale.

9.4 Projection

9.4.1 A conformal projection on which a straight line approximates a great circle shall be used.

9.4.2 When a chart is drawn to scale, parallels and meridians shall be shown at suitable intervals.

9.4.3 Graduation marks shall be placed at consistent intervals along the neat lines.

9.5 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the identification of the standard departure route(s) — instrument as established in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part I, Section 3, Chapter 5.

9.6 Culture and topography

9.6.1 Where a chart is drawn to scale, generalised shore lines of all open water areas, large lakes and rivers shall be shown except where they conflict with data more applicable to the function of a chart.



9.7 Magnetic variation

Magnetic variation used in determining the magnetic bearings, tracks and radials shall be shown to the nearest degree.

9.8 Bearings, tracks and radials

9.8.1 Bearings, tracks and radials shall be magnetic, except as provided for in 9.8.2. Where bearings and tracks are additionally provided as true values for RNAV segments, they shall be shown in parentheses to the nearest tenth of a degree, e.g. 290° (294.9°T).

9.8.2 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

9.9 Aeronautical data

9.9.1 Aerodromes

9.9.1.1 The aerodrome of departure shall be shown by the runway pattern.

9.9.1.2 All aerodromes which affect the designated standard departure route — instrument shall be shown and identified. Where appropriate, the aerodrome runway patterns shall be shown.

9.9.2 Prohibited, restricted and danger areas

Prohibited, restricted and danger areas which may affect the execution of the procedures shall be shown with their identification and vertical limits.

9.9.3 Minimum sector altitude

9.9.3.1 The established minimum sector altitude shall be shown with a clear indication of the sector to which it applies.

9.9.3.2 Where the minimum sector altitude has not been established, a chart shall be drawn to scale and area minimum altitudes shall be shown within quadrilaterals formed by the parallels and meridians. Area minimum altitudes shall also be shown in those parts of a chart not covered by the minimum sector altitude.

9.9.4 Air traffic services system

9.9.4.1 The components of the established relevant air traffic services system shall be shown.

9.9.4.1.1 The components shall comprise the following:

- (a) a graphic portrayal of each standard departure route — instrument, including:
 - (1) for departure procedures designed specifically for helicopters, the term “CAT H” shall be depicted in the departure chart plan view;
 - (2) route designator;
 - (3) significant points defining the route;



- (4) track or radial to the nearest degree along each segment of the route;
- (5) distances to the nearest kilometre or nautical mile between significant points;
- (6) minimum obstacle clearance altitudes, along the route or route segments and altitudes required by the procedure to the nearest higher 50 m or 100 ft and flight level restrictions where established;
- (7) where a chart is drawn to scale and vectoring on departure is provided, established minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;

Note 1: Where ATS surveillance systems are used to vector aircraft to or from significant points on a published standard departure route, the relevant procedures is to be shown on the Standard Departure Chart — Instrument (SID) — ICAO unless excessive chart clutter will result.

Note 2: Where excessive chart clutter will result, an ATC Surveillance Minimum Altitude Chart — ICAO is to be provided (see Chapter 21), in which case the elements indicated by 9.9.4.1.1, a) 6), need not be duplicated on the Standard Departure Chart — Instrument (SID) — ICAO.

- (b) the radio navigation aid(s) associated with the route(s) including:
 - (1) [when the radio navigation aid is used for conventional navigation;
 - (i) plain language name;
 - (ii) identification;
 - (iii) Morse code;
 - (iv) frequency;
 - (v) geographical coordinates in degrees, minutes and seconds; and
 - (vi) for DME, the channel and the elevation of the transmitting antenna of the DME to the nearest 30 m (100 ft);
 - (2) when the radio navigation aid is used as a significant point for area navigation;
 - (i) plain language name;
 - (ii) identification;
- (c) significant points not marked by the position of a radio navigation aid including:
 - (1) when the significant point is used for conventional navigation:
 - (i) name-code;
 - (ii) geographical coordinates in degrees, minutes and seconds;



- (iii) bearing to the nearest tenth of a degree from the reference radio navigation aid;
 - (iv) distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference radio navigation aid; and
 - (v) identification of the reference radio navigation aid;
- (2) when the significant point is used for area navigation:
- (i) name-code;]
- (d) applicable holding patterns;
 - (e) transition altitude/height to the nearest higher 300 m or 1000 ft;
 - (f) the position and height of close-in obstacles which penetrate the obstacle identification surface (OIS). A note shall be included whenever close-in obstacles penetrating the OIS exist but which were not considered for the published procedure design gradient;
 - (g) area speed restrictions, where established;
 - (h) the designation of the navigation specification(s) including any limitations, where established;
 - (i) all compulsory and “on-request” reporting points;
 - (j) radio communication procedures, including:
 - (1) call sign(s) of ATS unit(s);
 - (2) frequency and, if applicable, SATVOICE number;
 - (3) transponder setting, where appropriate;
 - (k) an indication of “flyover” significant points.
- 9.9.4.2 A textual description of standard departure route(s) — instrument (SID) and relevant communication failure procedures shall be provided and, whenever feasible, is to be shown on a chart or on the same page which contains a chart.

9.9.4.3 Aeronautical database requirements

Appropriate data to support navigation database coding shall be published in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part III, Section 5, Chapter 2, 2.1, on the back of a chart or as a separate, properly referenced sheet.



CHAPTER 10

STANDARD ARRIVAL CHART — INSTRUMENT (STAR) — ICAO

10.1 Function

10.1.1 This chart shall provide the flight crew with information to enable it to comply with the designated standard arrival route— instrument from the en-route phase to the approach phase.

Note 1: Standard arrival routes — instrument are to be interpreted as including “standard descent profiles”, “continuous descent approach”, and other non-standard descriptions. In the case of a standard descent profile, the depiction of a cross-section is not required.

Note 2: Provisions governing the identification of standard arrival routes are in Annex 11, Appendix 3; guidance material relating to the establishment of such routes is contained in the Air Traffic Services Planning Manual (Doc 9426).

10.2 Availability

The Standard Arrival Chart - Instrument (STAR) - ICAO shall be made available wherever a standard arrival route - instrument has been established and cannot be shown with sufficient clarity on the Area Chart.

10.3 Coverage and scale

10.3.1 The coverage of a chart shall be sufficient to indicate the points where the en-route phase ends and the approach phase begins.

10.3.2 If a chart is drawn to scale, a scale-bar shall be shown.

10.3.3 When a chart is not drawn to scale, the annotation “NOT TO SCALE” shall be shown and the symbol for scale break shall be used on tracks and other aspects of a chart which are too large to be drawn to scale.

10.4 Projection

10.4.1 A conformal projection on which a straight line approximates a great circle shall be used.

10.4.2 When a chart is drawn to scale, parallels and meridians shall be shown at suitable intervals.

10.4.3 Graduation marks shall be placed at consistent intervals along the neat lines.

10.5 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome, and the identification of the standard arrival route(s) — instrument as established in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part I, Section 4, Chapter 2.

10.6 Culture and topography

10.6.1 Where a chart is drawn to scale, generalised shore lines of all open water areas, large lakes and rivers shall be shown except where they conflict with data more applicable to the function of a chart.



10.6.2 To improve situational awareness in areas where significant relief exists, charts are to be drawn to scale and all relief exceeding 300 m (1000 ft) above the aerodrome elevation is to be shown by smoothed contour lines, contour values and layer tints printed in brown. Appropriate spot elevations, including the highest elevation within each top contour line, are to be shown printed in black. Obstacles must also be shown.

10.7 Magnetic variation

Magnetic variation used in determining the magnetic bearings, tracks and radials shall be shown to the nearest degree.

10.8 Bearings, tracks and radials

10.8.1 Bearings, tracks and radials shall be magnetic, except as provided for in 10.8.2. Where bearings and tracks are additionally provided as true values for RNAV segments, they shall be shown in parentheses to the nearest tenth of a degree, e.g. 290° (294.9°T).

10.8.2 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

10.9 Aeronautical data

10.9.1 Aerodromes

10.9.1.1 The aerodrome of landing shall be shown by the runway pattern.

10.9.1.2 All aerodromes which affect the designated standard arrival route — instrument shall be shown and identified. Where appropriate, the aerodrome runway patterns shall be shown.

10.9.2 Prohibited, restricted and danger areas

Prohibited, restricted and danger areas which may affect the execution of the procedures shall be shown with their identification and vertical limits.

10.9.3 Minimum sector altitude

10.9.3.1 The established minimum sector altitude shall be shown with a clear indication of the sector to which it applies.

10.9.3.2 Where the minimum sector altitude has not been established, a chart shall be drawn to scale and area minimum altitudes shall be shown within quadrilaterals formed by the parallels and meridians. Area minimum altitudes shall also be shown in those parts of a chart not covered by the minimum sector altitude.

10.9.4 Air traffic services system

10.9.4.1 The components of the established relevant air traffic services system shall be shown.

10.9.4.1.1 The components shall comprise the following:

- (a) a graphic portrayal of each standard arrival route — instrument, including:
 - (1) route designator;



- (2) significant points defining the route;
 - (3) track or radial to the nearest degree along each segment of the route;
 - (4) distances to the nearest kilometre or nautical mile between significant points;
 - (5) minimum obstacle clearance altitudes, along the route or route segments and altitudes required by the procedure to the nearest higher 50 m or 100 ft and flight level restrictions where established;
 - (6) where a chart is drawn to scale and vectoring on arrival is provided, established minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;
- (b) the radio navigation aid(s) associated with the route(s) including:
- (1) [when the radio navigation aid is used for conventional navigation;
 - (i) plain language name;
 - (ii) identification;
 - (iii) Morse code;
 - (iv) frequency;
 - (v) geographical coordinates in degrees, minutes and seconds; and
 - (vi) for DME, the channel and the elevation of the transmitting antenna of the DME to the nearest 30 m (100 ft);
 - (2) when the radio navigation aid is used as a significant point for area navigation;
 - (i) plain language name;
 - (ii) identification;
- (c) significant points not marked by the position of a radio navigation aid including:
- (1) when the significant point is used for conventional navigation:
 - (i) name-code;
 - (ii) geographical coordinates in degrees, minutes and seconds;
 - (iii) bearing to the nearest tenth of a degree from the reference radio navigation aid;
 - (iv) distance to the nearest two-tenths of a kilometre (tenth of a nautical mile) from the reference radio navigation aid; and
 - (v) identification of the reference radio navigation aid;
 - (2) when the significant point is used for area navigation:



- (i) name-code;]
- (d) applicable holding patterns;
- (e) transition altitude/height to the nearest higher 300 m or 1000 ft;
- (f) area speed restrictions, where established;
- (g) the designation of the navigation specification(s) including any limitations, where established;
- (h) all compulsory and “on-request” reporting points;
- (i) radio communication procedures, including:
 - (1) call sign(s) of ATS unit(s);
 - (2) frequency and, if applicable, SATVOICE number;
 - (3) transponder setting, where appropriate;
- (j) an indication of “flyover” significant waypoints; and
- (k) for arrival procedures to an instrument approach designed specifically for helicopters, the term “CAT H” shall be depicted in the arrival chart plan view.

10.9.4.2 Aeronautical database requirements

Appropriate data to support navigation database coding shall be published in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part III, Section 5, Chapter 2, 2.2, on the verso of a chart or as a separate, properly referenced sheet.



CHAPTER 11

INSTRUMENT APPROACH CHART — ICAO

11.1 Function

1.11.1 This chart shall provide flight crews with information which will enable them to perform an approved instrument approach procedure to the runway of intended landing including the missed approach procedure and, where applicable, associated holding patterns.

Note: Detailed criteria for the establishment of instrument approach procedures and the resolutions of associated altitudes/heights are contained in the Procedures for Air Navigation Services — Aircraft Operations (PANS-OPS, Doc 8168).

11.2 Availability

11.2.1 Instrument Approach Charts — ICAO shall be made available for all aerodromes used by international civil aviation where instrument approach procedures have been established by the State concerned.

11.2.2 A separate Instrument Approach Chart — ICAO shall normally be provided for each precision approach procedure established by the State.

11.2.3 A separate Instrument Approach Chart — ICAO shall normally be provided for each non-precision approach procedure established by the State.

Note: A single precision or non-precision approach procedure chart may be provided to portray more than one approach procedure when the procedures for the intermediate approach, final approach and missed approach segments are identical.

11.2.4 When the values for track, time or altitude differ between categories of aircraft on other than the final approach segment of the instrument approach procedures and the listing of these differences on a single chart could cause clutter or confusion, more than one chart shall be provided.

Note: For categories of aircraft, see Procedures for Air Navigation Services — Aircraft Operations (PANS-OPS, Doc 8168), Volume II, Part I, Section 4, Chapter 9.

11.2.5 Instrument Approach Charts — ICAO shall be revised whenever information essential to safe operation becomes out of date.

11.3 Coverage and scale

11.3.1 The coverage of a chart shall be sufficient to include all segments of the instrument approach procedure and such additional areas as may be necessary for the type of approach intended.

11.3.2 The scale selected shall ensure optimum legibility consistent with:

- (a) the procedure shown on a chart;
- (b) sheet size.

11.3.3 A scale indication shall be given.



- 11.3.3.1 Except where this is not practicable, a distance circle with a radius of 20 km (10 NM) centred on a DME located on or close to the aerodrome, or on the aerodrome reference point where no suitable DME is available, shall be shown; its radius shall be indicated on the circumference.
- 11.3.3.2 A distance scale should be shown directly below the profile.

11.4 Format

The sheet size should be 210 x 148 mm (8.27 x 5.82 in).

11.5 Projection

- 11.5.1 A conformal projection on which a straight line approximates a great circle shall be used.
- 11.5.2 Graduation marks should be placed at consistent intervals along the neat lines.

11.6 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome serves, the name of the aerodrome and the identification of the instrument approach procedure as established in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part I, Section 4, Chapter 9.

Note: The identification of the instrument approach procedure is provided by the procedures specialist.

11.7 Culture and topography

- 11.7.1 Culture and topographic information pertinent to the safe execution of the instrument approach procedure, including the missed approach procedure, associated holding procedures and visual manoeuvring (circling) procedure when established, shall be shown. Topographic information shall be named, only when necessary, to facilitate the understanding of such information, and the minimum shall be a delineation of land masses and significant lakes and rivers.
- 11.7.2 Relief shall be shown in a manner best suited to the particular elevation characteristics of the area. In areas where relief exceeds 1 200 m (4000 ft) above the aerodrome elevation within the coverage of a chart or 600 m (2000 ft) within 11 km (6 NM) of the aerodrome reference point or when final approach or missed approach procedure gradient is steeper than optimal due to terrain, all relief exceeding 150 m (500 ft) above the aerodrome elevation shall be shown by smoothed contour lines, contour values and layer tints printed in brown. Appropriate spot elevations, including the highest elevation within each top contour line, shall also be shown printed in black.

Note 1: The next higher suitable contour line appearing on base topographic maps exceeding 150 m (500 ft) above the aerodrome elevation may be selected to start layer tinting.

Note 2: An appropriate brown colour, on which half-tone layer tinting is to be based, is specified in ICAO Annex 4, Appendix 3 — Colour Guide for contours and topographic features.

Note 3: Appropriate spot elevations are those provided by the procedures specialist.



11.7.3 In areas where relief is lower than specified in 11.7.2, all relief exceeding 150 m (500 ft) above the aerodrome elevation should be shown by smoothed contour lines, contour values and layer tints printed in brown. Appropriate spot elevations, including the highest elevation within each top contour line, should also be shown printed in black.

Note 1: The next higher suitable contour line appearing on base topographic maps exceeding 150 m (500 ft) above the aerodrome elevation may be selected to start layer tinting.

Note 2: An appropriate brown colour, on which half-tone layer tinting is to be based, is specified in ICAO Annex 4, Appendix 3 — Colour Guide for contours and topographic features.

Note 3: Appropriate spot elevations are those provided by the procedures specialist.

11.8 Magnetic variation

11.8.1 The magnetic variation should be shown.

11.8.2 When shown, the value of the variation, indicated to the nearest degree, shall agree with that used in determining magnetic bearings, tracks and radials.

11.9 Bearings, tracks and radials

11.9.1 Bearings, tracks and radials shall be magnetic, except as provided for in 11.9.2. Where bearings and tracks are additionally provided as true values for RNAV segments, they shall be shown in parentheses to the nearest tenth of a degree, e.g. 290° (294.9°T).

Note: A note to this effect may be included on a chart.

11.9.2 In areas of high latitude, where it is determined by the appropriate authority that reference to Magnetic North is impractical, another suitable reference, i.e. True North or Grid North, should be used.

11.9.3 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

11.10 Aeronautical data

11.10.1 Aerodromes

11.10.1.1 All aerodromes which show a distinctive pattern from the air shall be shown by the appropriate symbol. Abandoned aerodromes shall be identified as abandoned.

11.10.1.2 The runway pattern, at a scale sufficiently large to show it clearly, shall be shown for:

- (a) the aerodrome on which the procedure is based;
- (b) aerodromes affecting the traffic pattern or so situated as to be likely, under adverse weather conditions, to be mistaken for the aerodrome of intended landing.

11.10.1.3 The aerodrome elevation shall be shown to the nearest metre or foot in a prominent position on a chart.



11.10.1.4 The threshold elevation or, where applicable, the highest elevation of the touchdown zone shall be shown to the nearest metre or foot.

11.10.2 Obstacles

11.10.2.1 Obstacles shall be shown on the plan view of a chart.

Note: Appropriate obstacles are those provided by the procedures specialist.

11.10.2.2 *If one or more obstacles are the determining factor of an obstacle clearance altitude/height, those obstacles should be identified.*

11.10.2.3 The elevation of the top of obstacles shall be shown to the nearest (next higher) metre or foot.

11.10.2.4 *The heights of obstacles above a datum other than mean sea level (see 11.10.2.3) should be shown. When shown, they should be given in parentheses on a chart.*

11.10.2.5 When the heights of obstacles above a datum other than mean sea level are shown, the datum shall be the aerodrome elevation except that, at aerodromes having an instrument runway (or runways) with a threshold elevation more than 2 m (7 ft) below the aerodrome elevation, a chart datum shall be the threshold elevation of the runway to which the instrument approach is related.

11.10.2.6 Where a datum other than mean sea level is used, it shall be stated in a prominent position on a chart.

11.10.2.7 Where an obstacle free zone has not been established for a precision approach runway Category I, this shall be indicated. []

11.10.3 Prohibited, restricted and danger areas

Prohibited areas, restricted areas, and danger areas which may affect the execution of the procedures shall be shown with their identification and vertical limits.

11.10.4 Radio communication facilities and navigation aids

11.10.4.1 Radio navigation aids required for the procedures together with their frequencies, identifications and track-defining characteristics, if any, shall be shown. In the case of a procedure in which more than one station is located on the final approach track, the facility to be used for track guidance for final approach shall be clearly identified. In addition, consideration shall be given to the elimination from the approach chart of those facilities that are not used by the procedure.

11.10.4.1.1 [When a radio navigation aid is used as a significant point for area navigation, only its plain language name and identification shall be shown.]

11.10.4.2 The initial approach fix (IAF), the intermediate approach fix (IF), the final approach fix (FAF) (or final approach point (FAP) for an ILS approach procedure), the missed approach point (MAPt), where established, and other essential fixes or points comprising the procedure shall be shown and identified.



11.10.4.3 [When the final approach fix is used for conventional navigation (or final approach point for an ILS approach procedure), it should be identified with its geographical coordinates in degrees, minutes and seconds.]

11.10.4.4 Radio navigation aids that might be used in diversionary procedures together with their track-defining characteristics, if any, shall be shown or indicated on a chart.

11.10.4.5 Radio communication frequencies, including call signs that are required for the execution of the procedures shall be shown.

11.10.4.6 When required by the procedures, the distance to the aerodrome from each radio navigation aid concerned with the final approach shall be shown to the nearest kilometre or nautical mile. When no track-defining aid indicates the bearing of the aerodrome, the bearing shall also be shown to the nearest degree.

11.10.5 Minimum sector altitude or terminal arrival altitude

The minimum sector altitude or terminal arrival altitude established by the competent authority shall be shown, with a clear indication of the sector to which it applies.

11.10.6 Portrayal of procedure tracks

11.10.6.1 The plan view shall show the following information in the manner indicated:

- (a) the approach procedure track by an arrowed continuous line indicating the direction of flight;
- (b) the missed approach procedure track by an arrowed broken line;
- (c) any additional procedure track, other than those specified in a) and b), by an arrowed dotted line;
- (d) bearings, tracks, radials to the nearest degree and distances to the nearest two-tenths of a kilometre or tenth of a nautical mile or times required for the procedure;
- (e) where no track-defining aid is available, the magnetic bearing to the nearest degree to the aerodrome from the radio navigation aids concerned with the final approach;
- (f) the boundaries of any sector in which visual manoeuvring (circling) is prohibited;
- (g) where specified, the holding pattern and minimum holding altitude/height associated with the approach and missed approach;
- (h) caution notes where required, prominently displayed on the face of a chart;
- (i) an indication of “flyover” significant points.

11.10.6.2 The plan view should show the distance to the aerodrome from each radio navigation aid concerned with the final approach.

11.10.6.3 A profile shall be provided normally below the plan view showing the following data:

- (a) the aerodrome by a solid block at aerodrome elevation;



- (b) the profile of the approach procedure segments by an arrowed continuous line indicating the direction of flight;
- (c) the profile of the missed approach procedure segment by an arrowed broken line and a description of the procedure;
- (d) the profile of any additional procedure segment, other than those specified in b) and c), by an arrowed dotted line;
- (e) bearings, tracks, radials to the nearest degree and distances to the nearest two-tenths of a kilometre or tenth of a nautical mile or times required for the procedure;
- (f) altitudes/heights required by the procedures, including transition altitude, procedure altitudes/heights and heliport crossing height (HCH), where established;
- (g) limiting distance to the nearest kilometre or nautical mile on procedure turn, when specified;
- (h) the intermediate approach fix or point, on procedures where no course reversal is authorised;
- (i) a line representing the aerodrome elevation or threshold elevation, as appropriate, extended across the width of a chart including a distance scale with its origin at the runway threshold.

11.10.6.4 Heights required by procedures should be shown in parentheses, using the height datum selected in accordance with 11.10.2.5.

11.10.6.5 The profile view should include a ground profile or a minimum altitude/height portrayal as follows:

- (a) a ground profile shown by a solid line depicting the highest elevations of the relief occurring within the primary area of the final approach segment. The highest elevations of the relief occurring in the secondary areas of the final approach segment shown by a dashed line; or
- (b) minimum altitudes/heights in the intermediate and final approach segments indicated within bounded shaded blocks.

Note 1: For the ground profile portrayal, actual templates of the primary and secondary areas of the final approach segment are provided to the cartographer by the procedures specialist.

Note 2: The minimum altitude/height portrayal is intended for use on charts depicting non-precision approaches with a final approach fix.

11.10.7 Aerodrome operating minima

11.10.7.1 Aerodrome operating minima when established by the State shall be shown.

11.10.7.2 The obstacle clearance altitudes/heights for the aircraft categories for which the procedure is designed shall be shown; for precision approach procedures, additional OCA/H for Cat D_L aircraft (wing span between 65 m and 80 m and/or vertical distance between the flight path of the wheels and the glide path antenna between 7 m and 8 m) shall be published, when necessary.



11.10.8 Supplementary information

11.10.8.1 When the missed approach point is defined by:

- a distance from the final approach fix, or
- a facility or a fix and the corresponding distance from the final approach fix,

the distance to the nearest two-tenths of a kilometre or tenth of a nautical mile and a table showing ground speeds and times from the final approach fix to the missed approach point shall be shown.

11.10.8.2 When DME is required for use in the final approach segment, a table showing altitudes/heights for each 2 km or 1 NM, as appropriate, shall be shown. The table shall not include distances which would correspond to altitudes/heights below the OCA/H.

11.10.8.3 For procedures in which DME is not required for use in the final approach segment but where a suitably located DME is available to provide advisory descent profile information, a table showing the altitudes/heights should be included.

11.10.8.4 A rate of descent table should be shown.

11.10.8.5 For non-precision approach procedures with a final approach fix, the final approach descent gradient to the nearest one-tenth of a per cent and, in parentheses, descent angle to the nearest one-tenth of a degree shall be shown.

11.10.8.6 For precision approach procedures and approach procedures with vertical guidance, the reference datum height to the nearest half metre or foot and the glide path/elevation/vertical path angle to the nearest one-tenth of a degree shall be shown.

11.10.8.7 When a final approach fix is specified at the final approach point for ILS, a clear indication shall be given whether it applies to the ILS, the associated ILS localizer only procedure, or both. In the case of MLS, a clear indication shall be given when an FAF has been specified at the final approach point.

11.10.8.8 If the final approach descent gradient/angle for any type of instrument approach procedure exceeds the maximum value specified in the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, a cautionary note shall be included.

11.10.8.9 [A note shall be included on the chart indicating the approach procedures that are authorized for simultaneous independent or dependent operations. The note shall include the runway(s) involved and if they are closely spaced.]

11.10.9 Aeronautical database requirements

Appropriate data to support navigation database coding shall be published in accordance with the *Procedures for Air Navigation Services — Aircraft Operations* (PANS-OPS, Doc 8168), Volume II, Part III, Section 5, Chapter 2, 2.3, for RNAV procedures and Volume II, Part I, Section 4, Chapter 9, 9.4.1.3, for non-RNAV procedures, on the verso of a chart or as a separate, properly referenced sheet.



This Page Intentionally Left Blank



CHAPTER 12

VISUAL APPROACH CHART — ICAO

12.1 Function

This chart shall provide flight crews with information which will enable them to transit from the en-route/descent to approach phases of flight to the runway of intended landing by means of visual reference.

12.2 Availability

The Visual Approach Chart — ICAO shall be made available in the manner prescribed in 1.3.2 for all aerodromes used by international civil aviation where:

- (a) only limited navigation facilities are available; or
- (b) radio communication facilities are not available; or
- (c) no adequate aeronautical charts of the aerodrome and its surroundings at 1:500,000 or greater scale are available; or
- (d) visual approach procedures have been established.

12.3 Scale

12.3.1 The scale shall be sufficiently large to permit depiction of significant features and indication of the aerodrome layout.

12.3.2 When an Instrument Approach Chart is available for a given aerodrome, the Visual Approach Chart shall be drawn to the same scale.

12.4 Format

The sheet size shall be 210 x 148 mm (8.27 x 5.82 in).

12.5 Projection

12.5.1 A conformal projection on which a straight line approximates a great circle shall be used.

12.6 Identification

A chart shall be identified by the name of the city or town which the aerodrome serves and the name of the aerodrome.

12.7 Culture and topography

12.7.1 Natural and cultural landmarks shall be shown (e.g. bluffs, cliffs, sand dunes, cities, towns, roads, railroads, isolated lighthouses).

12.7.1.1 Geographical place names shall only be included when they are required to avoid confusion or ambiguity.

12.7.2 Shore lines, lakes, rivers and streams shall be shown.



12.7.3 Relief shall be shown in a manner best suited to the particular elevation and obstacle characteristics of the area covered by a chart.

12.7.4 The figures relating to different reference levels shall be clearly differentiated in their presentation.

12.8 Magnetic variation

The magnetic variation shall be shown.

12.9 Bearings, tracks and radials

12.9.1 Bearings, tracks and radials shall be magnetic except as provided for in 12.9.2.

12.9.2 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

12.10 Aeronautical data

12.10.1 Aerodromes

12.10.1.1 All aerodromes shall be shown by the runway pattern. Restrictions on the use of any landing direction shall be indicated. Where there is any risk of confusion between two neighbouring aerodromes, this shall be indicated. Abandoned aerodromes shall be identified as abandoned.

12.10.1.2 The aerodrome elevation shall be shown in a prominent position on a chart.

12.10.2 Obstacles

12.10.2.1 Obstacles shall be shown and identified.

12.10.2.2 The elevation of the top of obstacles shall be shown to the nearest (next higher) metre or foot.

12.10.2.2.1 When the heights of obstacles are shown, the height datum shall be stated in a prominent position on a chart and the heights shall be given in parentheses on a chart.

12.10.3 Prohibited, restricted and danger areas

Prohibited areas, restricted areas, and danger areas shall be depicted with their identification and vertical limits.

12.10.4 Designated airspace

Where applicable, control zones and aerodrome traffic zones shall be depicted with their vertical limits and the appropriate class of airspace.

12.10.5 Visual approach information

12.10.5.1 Visual approach procedures shall be shown where applicable.

12.10.5.2 Visual aids for navigation shall be shown as appropriate.



12.10.5.3 Location and type of the visual approach slope indicator systems with their nominal approach slope angle(s), minimum eye height(s) over the threshold of the on-slope signal(s), and where the axis of the system is not parallel to the runway centre line, the angle and direction of displacement, i.e. left or right, shall be shown.

12.10.6 Supplementary information

12.10.6.1 Radio navigation aids together with their frequencies and identifications shall be shown as appropriate.

12.10.6.2 Radio communication facilities with their frequencies shall be shown as appropriate.



This Page Intentionally Left Blank

**CHAPTER 13****AERODROME/HELIPORT CHART — ICAO****13.1 Function**

13.1.1 This chart shall provide flight crews with information which will facilitate the ground movement of aircraft:

- (a) from the aircraft stand to the runway; and
- (b) from the runway to the aircraft stand; and helicopter movement:
- (c) from the helicopter stand to the touchdown and lift-off area and to the final approach and take-off area;
- (d) from the final approach and take-off area to the touchdown and lift-off area and to the helicopter stand;
- (e) along helicopter ground and air taxiways; and
- (f) along air transit routes;

13.1.2 It shall also provide essential operational information at the aerodrome/heliport.

13.2 Availability

13.2.1 The Aerodrome/Heliport Chart — ICAO shall be made available in the manner prescribed in 1.3.2 for all aerodromes/heliports used by international civil aviation.

13.3 Coverage and scale

13.3.1 The coverage and scale shall be sufficiently large to show clearly all the elements listed in 13.6.1.

13.3.2 A linear scale shall be shown.

13.4 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome/heliport serves and the name of the aerodrome/heliport.

13.5 Magnetic variation

True and Magnetic North arrows and magnetic variation to the nearest degree and annual change of the magnetic variation shall be shown.

13.6 Aerodrome/heliport data

13.6.1 This chart shall show:

- (a) geographical coordinates in degrees, minutes and seconds for the aerodrome/heliport reference point;



- (b) elevations, to the nearest metre or foot, of the aerodrome/heliport and apron (altimeter checkpoint locations) where applicable; and for non-precision approaches, elevations and geoid undulations of runway thresholds and the geometric centre of the touchdown and lift-off area;
- (c) elevations and geoid undulations, to the nearest half-metre or foot, of the precision approach runway threshold, the geometric centre of the touchdown and lift-off area, and at the highest elevation of the touchdown zone of a precision approach runway;
- (d) all runways including those under construction with designation number, length and width to the nearest metre, bearing strength, displaced thresholds, stopways, clearways, runway directions to the nearest degree magnetic, type of surface and runway markings;
- (e) all aprons, with aircraft/helicopter stands, lighting, markings and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems, type of surface for heliports, and bearing strengths or aircraft type restrictions where the bearing strength is less than that of the associated runways;
- (f) geographical coordinates in degrees, minutes and seconds for thresholds, geometric centre of touchdown and lift-off area and/or thresholds of the final approach and take-off area (where appropriate);
- (g) all taxiways, helicopter air and ground taxiways with type of surface, helicopter air transit routes, with designations, width, lighting, markings (including runway-holding positions and, where established, intermediate holding positions), stop bars, other visual guidance and control aids, and bearing strength or aircraft type restrictions where the bearing strength is less than that of the associated runways;
- (h) where established, hot spot locations with additional information properly annotated;
- (i) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points and aircraft stands;
- (j) where established, standard routes for taxiing aircraft with their designators;
- (k) the boundaries of the air traffic control service;
- (l) position of runway visual range (RVR) observation sites;
- (m) approach and runway lighting;
- (n) location and type of the visual approach slope indicator systems with their nominal approach slope angle(s), minimum eye height(s) over the threshold of the on-slope signal(s), and where the axis of the system is not parallel to the runway centre line, the angle and direction of the displacement, i.e. left or right;
- (o) relevant communication facilities listed with their channels and, if applicable, logon address and SATVOICE number;
- (p) obstacles to taxiing;
- (q) aircraft servicing areas and buildings of operational significance;



- (r) VOR checkpoint and radio frequency of the aid concerned;
- (s) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such.

13.6.2 [For aerodromes accommodating aeroplanes with folding wing tips, the location where the wing tips may be safely extended should be shown on the chart.]

13.6.3 In addition to the items in 13.6.1 relating to heliports, a chart shall show:

- (a) heliport type;
- (b) touchdown and lift-off area including dimensions to the nearest metre, slope, type of surface and bearing strength in tonnes;
- (c) final approach and take-off area including type, true bearing to the nearest degree, designation number (where appropriate), length and width to the nearest metre, slope and type of surface;
- (d) safety area including length, width and type of surface;
- (e) helicopter clearway including length and ground profile;
- (f) obstacles including type and elevation of the top of the obstacles to the nearest (next higher) metre or foot;
- (g) visual aids for approach procedures, marking and lighting of final approach and take-off area, and of touchdown and lift-off area;
- (h) declared distances to the nearest metre for heliports, where relevant, including:
 - (1) take-off distance available;
 - (2) rejected take-off distance available;
 - (3) landing distance available.



This Page Intentionally Left Blank



CHAPTER 14

AERODROME GROUND MOVEMENT CHART — ICAO

14.1 Function

This supplementary chart shall provide flight crews with detailed information to facilitate the ground movement of aircraft to and from the aircraft stands and the parking/docking of aircraft.

14.2 Availability

The Aerodrome Ground Movement Chart — ICAO shall be made available in the manner prescribed in 1.3.2 where, due to congestion of information, details necessary for the ground movement of aircraft along the taxiways to and from the aircraft stands cannot be shown with sufficient clarity on an Aerodrome/Heliport Chart — ICAO.

14.3 Coverage and scale

14.3.1 The coverage and scale shall be sufficiently large to show clearly all the elements listed in 14.6.

14.3.2 A linear scale shall be shown.

14.4 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome serves and the name of the aerodrome.

14.5 Magnetic variation

14.5.1 A True North arrow shall be shown.

14.5.2 Magnetic variation to the nearest degree and its annual change shall be shown.

Note: This chart need not be True North orientated.

14.6 Aerodrome data

14.6.1 This chart shall show in a similar manner all the information on the Aerodrome/Heliport Chart — ICAO relevant to the area depicted, including:

- (a) apron elevation to the nearest metre or foot;
- (b) aprons with aircraft stands, bearing strengths or aircraft type restrictions, lighting, marking and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems;
- (c) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for aircraft stands;
- (d) taxiways with designations, width to the nearest metre, bearing strength or aircraft type restrictions where applicable, lighting, markings (including runway-holding positions and, where established, intermediate holding positions), stop bars, and other visual guidance and control aids;



- (e) where established, hot spot locations with additional information properly annotated;

Note: Additional information regarding hot spots are to be shown in tabular form on the face or back of a chart.

- (f) where established, standard routes for taxiing aircraft, with their designators;
- (g) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points;
- (h) the boundaries of the air traffic control service;
- (i) relevant communication facilities listed with their channels and, if applicable, logon address;
- (j) obstacles to taxiing;
- (k) aircraft servicing areas and buildings of operational significance;
- (l) VOR checkpoint and radio frequency of the aid concerned;
- (m) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such.

14.6.2 [For aerodromes accommodating aeroplanes with folding wing tips, the location where the wing tips may be safely extended should be shown on the chart.]



CHAPTER 15

AIRCRAFT PARKING/DOCKING CHART — ICAO

15.1 Function

This supplementary chart shall provide flight crews with detailed information to facilitate the ground movement of aircraft between the taxiways and the aircraft stands and the parking/docking of aircraft.

15.2 Availability

The Aircraft Parking/Docking Chart — ICAO shall be made available in the manner prescribed in where, due to the complexity of the terminal facilities, the information cannot be shown with sufficient clarity on the Aerodrome/Heliport Chart — ICAO or on the Aerodrome Ground Movement Chart — ICAO.

15.3 Coverage and scale

15.3.1 The coverage and scale shall be sufficiently large to show clearly all the elements listed in 15.6.

15.3.2 A linear scale shall be shown.

15.4 Identification

A chart shall be identified by the name of the city or town or area which the aerodrome serves and the name of the aerodrome.

15.5 Magnetic variation

15.5.1 A True North arrow shall be shown.

15.5.2 Magnetic variation to the nearest degree and its annual change shall be shown.

Note: This chart need not be True North orientated.

15.6 Aerodrome data

This chart shall show in a similar manner all the information on the Aerodrome/Heliport Chart — ICAO and the Aerodrome Ground Movement Chart — ICAO relevant to the area depicted, including:

- (a) apron elevation to the nearest metre or foot;
- (b) aprons with aircraft stands, bearing strengths or aircraft type restrictions, lighting, marking and other visual guidance and control aids, where applicable, including location and type of visual docking guidance systems;
- (c) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for aircraft stands;
- (d) taxiway entries with designations, including runway-holding positions and, where established, intermediate holding positions, and stop bars;
- (e) where established, hot spot locations with additional information properly annotated;



Note: Additional information regarding hot spots is to be shown in tabular form on the face or back of a chart

- (f) geographical coordinates in degrees, minutes, seconds and hundredths of seconds for appropriate taxiway centre line points;
- (g) the boundaries of the air traffic control service;
- (h) relevant communication facilities listed with their channels and, if applicable, logon address;
- (i) obstacles to taxiing;
- (j) aircraft servicing areas and buildings of operational significance;
- (k) VOR checkpoint and radio frequency of the aid concerned;
- (l) any part of the depicted movement area permanently unsuitable for aircraft, clearly identified as such.



CHAPTER 16

WORLD AERONAUTICAL CHART — ICAO 1:1,000,000

16.1 Function

16.1.1 This chart shall provide information to satisfy the requirements of visual air navigation.

Note: This chart may also serve:

- (a) *as a basic aeronautical chart:*
 - (1) *when highly specialised charts lacking visual information do not provide essential data;*
 - (2) *to provide complete world coverage at a constant scale with a uniform presentation of planimetric data;*
 - (3) *in the production of other charts required by international civil aviation;*
- (b) *as a pre-flight planning chart.*

16.2 Availability

16.2.1 The World Aeronautical Chart — ICAO 1:1,000,000 shall be made available in the manner prescribed in 1.3.2 for all areas delineated in ICAO Annex 4, Appendix 5.

16.3 Scales

16.3.1 Linear scales for kilometres and nautical miles arranged in the following order:

- kilometres,
- nautical miles,

with their zero points in the same vertical line shall be shown in the margin.

16.3.2 A conversion scale (metres/feet) shall be shown in the margin.

16.4 Format

16.4.1 The title and marginal notes shall be in English

16.4.2 The information regarding the number of the adjoining sheets and the unit of measurement to express elevations shall be so located as to be clearly visible when the sheet is folded.

16.4.3 Whenever practicable, the sheet lines are to conform with those shown in the index in ICAO Annex 4, Appendix 5.

16.4.4 When overlaps are needed, these are to be provided by extending a chart area on the top and right side beyond the area given on the index. This overlap area shall contain all aeronautical, topographical, hydrographical and cultural information and extend up to 28 km (15 NM), if possible, but in any case from the limiting parallels and meridians of each chart to the neat line.



16.5 Projection

16.5.1 The projections shall be as follows:

- a) between the Equator and 80° latitude: the Lambert conformal conic projection, in separate bands for each tier of charts. The standard parallels for each 4° band shall be 40' south of the northern parallel and 40' north of the southern parallel;
- b) between 80° and 90° latitude: the Polar stereographic projection with scale matching that of the Lambert conformal conic projection at latitude 80°, except that in the northern hemisphere the Lambert conformal conic projection may be used between 80° and 84° latitude and the Polar stereographic projection between 84° and 90° with the scales matching at 84° North.

16.5.2 Graticules and graduations shall be shown as follows:

a) Parallels:

<i>Latitude</i>	<i>Distance between parallels</i>	<i>Graduations on parallels</i>
0° to 72°	30'	1'
72° to 84°	30'	5'
84° to 89°	30'	1°
89° to 90°	30'	5°
(Only on degree parallels from 72° to 89°)		

b) Meridians:

<i>Latitude</i>	<i>Interval between meridians</i>	<i>Graduations on meridians</i>
0° to 52°	30'	1'
52° to 72°	30'	1'
(Only on even numbered meridians)		
72° to 84°	1°	1'
84° to 89°	5°	1'
89° to 90°	15°	1'
(Only on every fourth meridian)		

16.5.3 The graduation marks at 1' and 5' intervals shall extend away from the Greenwich Meridian and from the Equator. Each 10' interval shall be shown by a mark on both sides of the graticule line.

16.5.4 All meridians and parallels shown shall be numbered in the borders of a chart. In addition, each parallel shall be numbered within the body of a chart in such a manner that the parallel can be readily identified when a chart is folded.

16.5.5 The name and basic parameters of the projection shall be indicated in the margin.

16.6 Identification

Sheet numbering shall be in conformity with the index in ICAO Annex 4, Appendix 5.



16.7 Culture and topography

16.7.1 Built-up areas

16.7.1.1 Cities, towns and villages shall be selected and shown according to their relative importance to visual air navigation.

16.7.1.2 Cities and towns of sufficient size are to be indicated by the outline of their built-up areas and not of their established city limits.

16.7.2 Railroads

16.7.2.1 All railroads having landmark value shall be shown.

16.7.3 Highways and roads

16.7.3.1 Road systems shall be shown in sufficient detail to indicate significant patterns from the air.

16.7.3.2 Roads are not to be shown in built-up areas unless they can be distinguished from the air as definite landmarks.

16.7.4 Landmarks

Natural and cultural landmarks, such as bridges, prominent transmission lines, permanent cable car installations, wind turbines, mine structures, forts, ruins, levees, pipelines, rocks, bluffs, cliffs, sand dunes, isolated lighthouses and lightships, are to be shown when considered to be of importance for visual navigation.

16.7.5 Political boundaries

International boundaries shall be shown. Un-demarcated and undefined boundaries shall be distinguished by descriptive notes.

16.7.6 Hydrography

16.7.6.1 All water features compatible with the scale of a chart comprising shore lines, lakes, rivers and streams (including those non-perennial in nature), salt lakes, glaciers and ice caps shall be shown.

16.7.6.2 The tint covering large open water areas is to be kept very light.

16.7.6.3 Reefs and shoals, including rocky ledges, tidal flats, isolated rocks, sand, gravel, stone and all similar areas, shall be shown by symbols when of significant landmark value.

Note: Groups of rocks are to be shown by a few representative rock symbols within the area.

16.7.7 Contours

16.7.7.1 Contours shall be shown. The selection of intervals shall be governed by the requirement to depict clearly the relief features required in air navigation.

16.7.7.2 The values of the contours used shall be shown.



16.7.8 Hypsometric tints

16.7.8.1 When hypsometric tints are used, the range of elevations for the tints shall be shown.

16.7.8.2 The scale of the hypsometric tints used on a chart shall be shown in the margin.

16.7.9 Spot elevations

16.7.9.1 Spot elevations shall be shown at selected critical points. The elevations selected shall always be the highest in the immediate vicinity and shall generally indicate the top of a peak, ridge, etc. Elevations in valleys and at lake surface levels which are of special value to the aviator shall be shown. The position of each selected elevation shall be indicated by a dot.

16.7.9.2 The elevation (in metres or feet) of the highest point on a chart and its geographical position to the nearest five minutes shall be indicated in the margin.

16.7.10 Incomplete or unreliable relief

16.7.10.1 Areas that have not been surveyed for contour information shall be labelled “Relief data incomplete”.

16.7.10.2 Charts on which spot elevations are generally unreliable shall bear a warning note prominently displayed on the face of a chart in the colour used for aeronautical information, as follows:

“Warning — The reliability of relief information on this chart is doubtful and elevations should be used with caution.”

16.7.11 Escarpments

Not applicable

16.7.12 Wooded areas

Wooded areas shall be depicted on charts only when they are considered to be significant features for navigation.

16.7.12.1 Where shown, the approximate extreme northern or southern limits of tree growth shall be indicated by a dashed black line and shall be appropriately labelled.

16.7.13 Date of topographic information

The date of latest information shown on the topographic base shall be indicated in the margin.

16.8 Magnetic variation

16.8.1 Isogonic lines shall be shown.

16.8.2 The date of the isogonic information shall be indicated in the margin.

16.9 Aeronautical data

16.9.1 General



Aeronautical data shown shall be kept to a minimum consistent with the use of a chart for visual navigation and the revision cycle (see 16.9.6).

16.9.2 Aerodromes

16.9.2.1 Land and water aerodromes and heliports shall be shown with their names, to the extent that they do not produce undesirable congestion on a chart, priority being given to those of greatest aeronautical significance.

16.9.2.2 The aerodrome elevation, the lighting available, the type of runway surface and the length of the longest runway or channel, shown in abbreviated form for each aerodrome in conformity with the example given in ICAO Annex 4, Appendix 2, provided they do not cause undesirable clutter on a chart, shall be indicated.

16.9.2.3 Abandoned aerodromes which are still recognisable as aerodromes from the air shall be shown and identified as abandoned.

16.9.3 Obstacles

16.9.3.1 Obstacles shall be shown.

16.9.3.2 When considered of importance to visual flight, prominent transmission lines, permanent cable car installations and wind turbines, which are obstacles, shall be shown.

16.9.4 Prohibited, restricted and danger areas Prohibited, restricted and danger areas shall be shown.

16.9.5 Air traffic services system

16.9.5.1 Significant elements of the air traffic services system including, where practicable, control zones, aerodrome traffic zones, control areas, flight information regions and other airspaces in which VFR flights operate shall be shown together with the appropriate class of airspace.

16.9.5.2 Where appropriate, the air defence identification zone (ADIZ) shall be shown and properly identified.

16.9.6 Radio navigation aids

Radio navigation aids shall be shown by the appropriate symbol and named, but excluding their frequencies, coded designators, times of operation and other characteristics unless any or all of this information which is shown is kept up to date by means of new editions of a chart.

16.9.7 Supplementary information

16.9.7.1 Aeronautical ground lights together with their characteristics or their identifications or both shall be shown.

16.9.7.2 Marine lights on outer prominent coastal or isolated features of not less than 28 km (15 NM) visibility range shall be shown:

- (a) where they are not less distinguishable than more powerful marine lights in the vicinity;
- (b) where they are readily distinguishable from other marine or other types of lights in the vicinity of built-up coastal areas;



- (c) where they are the only lights of significance available.



CHAPTER 17

AERONAUTICAL CHART — ICAO 1:500,000

17.1 Function

17.1.1 This chart shall provide information to satisfy the requirements of visual air navigation for low speed, short- or medium-range operations at low and intermediate altitudes.

Note 1: This chart may be used:

- (a) *to serve as a basic aeronautical chart;*
- (b) *to provide a suitable medium for basic pilot and navigation training;*
- (c) *to supplement highly specialised charts which do not provide essential visual information;*
- (d) *in pre-flight planning.*

Note 2: It is intended that these charts be provided for land areas where charts of this scale are required for civil air operations employing visual air navigation independently or in support of other forms of air navigation.

17.2 Availability

The Aeronautical Chart — ICAO 1:500,000 shall be made available in the manner prescribed in 1.3.2 for all areas delineated in ICAO Annex 4, Appendix 5.

Note: The selection of this scale as an alternative to the World Aeronautical Chart — ICAO 1:1,000,000 is covered by 16.2.1 and 16.2.2.

17.3 Scales

17.3.1 Linear scales for kilometres and nautical miles arranged in the following order:

- kilometres,
- nautical miles,

with their zero points in the same vertical line shall be shown in the margin.

17.3.1.1 The length of the linear scale shall be not less than 200 mm (8 in).

17.3.2 A conversion scale (metres/feet) shall be shown in the margin.

17.4 Format

17.4.1 The title and marginal notes shall be in English.

17.4.2 The information regarding the number of the adjoining sheets and the unit of measurement used to express elevation shall be so located as to be clearly visible when the sheet is folded.



17.5 Projection

17.5.1 A conformal (orthomorphic) projection shall be used.

17.5.2 Parallels shall be shown at intervals of 30’.

17.5.2.1 Meridians shall normally be shown at intervals of 30’

17.5.3 Graduation marks shall be shown at 1’ intervals along each whole degree meridian and parallel, extending away from the Greenwich Meridian and from the Equator. Each 10’ interval shall be shown by a mark on both sides of the graticule line.

17.5.4 All meridians and parallels shown shall be numbered in the borders of a chart.

17.5.5 The name and basic parameters of the projection shall be indicated in the margin.

17.6 Identification

17.6.1 Each sheet shall be identified by a name which should be that of the principal town or of a main geographical feature appearing on the sheet.

17.6.1.1 Where applicable, sheets shall also be identified by the reference number of the corresponding World Aeronautical Chart — ICAO 1:1,000,000, with the addition of one or more of the following letter suffixes indicating the quadrant or quadrants:

<i>Letter</i>	<i>Chart quadrant</i>
A	North-West
B	North-East
C	South-East
D	South-West

17.7 Culture and topography

17.7.1 Built-up areas

17.7.1.1 Cities, towns and villages shall be selected and shown according to their relative importance to visual air navigation.

17.7.1.2 Cities and towns of sufficient size are to be indicated by the outline of their built-up areas and not of their established city limits.

17.7.2 Railroads

17.7.2.1 All railroads having landmark value shall be shown.

17.7.2.2 Tunnels shall be shown when they serve as prominent landmarks.

17.7.3 Highways and roads

17.7.3.1 Road systems shall be shown in sufficient detail to indicate significant patterns from the air.



17.7.3.2 Roads are not to be shown in built-up areas unless they can be distinguished from the air as definite landmarks.

17.7.4 Landmarks

Natural and cultural landmarks, such as bridges, prominent transmission lines, permanent cable car installations, wind turbines, mine structures, lookout towers, forts, ruins, levees, pipelines, rocks, bluffs, cliffs, sand dunes, isolated lighthouses and lightships, are to be shown only when considered to be of importance for visual air navigation.

17.7.5 Political boundaries

International boundaries shall be shown. Un-demarcated and undefined boundaries shall be distinguished by descriptive notes.

17.7.6 Hydrography

17.7.6.1 All water features compatible with the scale of a chart comprising shore lines, lakes, rivers and streams (including those non-perennial in nature), salt lakes, glaciers and ice caps shall be shown.

17.7.6.2 The tint covering large open water areas shall be kept very light.

17.7.6.3 Reefs and shoals, including rocky ledges, tidal flats, isolated rocks, sand, gravel, stone and all similar areas, are to be shown by symbols when of significant landmark value.

Note: Groups of rocks are to be shown by a few representative rock symbols within the area.

17.7.7 Contours

17.7.7.1 Contours shall be shown. The selection of intervals shall be governed by the requirement to depict clearly the relief features required in air navigation.

17.7.7.2 The values of the contours used shall be shown.

17.7.8 Hypsometric tints

17.7.8.1 When hypsometric tints are used, the range of elevations for the tints shall be shown.

17.7.8.2 The scale of the hypsometric tints used on a chart shall be shown in the margin.

17.7.9 Spot elevations

17.7.9.1 Spot elevations shall be shown at selected critical points. The elevations selected shall always be the highest in the immediate vicinity and shall generally indicate the top of a peak, ridge, etc. Elevations in valleys and at lake surface levels which are of navigational value shall be shown. The position of each selected elevation shall be indicated by a dot.

17.7.9.2 The elevation (in metres or feet) of the highest point on a chart and its geographical position to the nearest five minutes shall be indicated in the margin.



17.7.10 Incomplete or unreliable relief

17.7.10.1 Areas that have not been surveyed for contour information shall be labelled “Relief data incomplete”.

17.7.10.2 Charts on which spot elevations are generally unreliable shall bear a warning note prominently displayed on the face of a chart in the colour used for aeronautical information, as follows:

“Warning — The reliability of relief information on this chart is doubtful and elevations should be used with caution.”

17.7.11 Escarpments

Not applicable

17.7.12 Wooded areas

17.7.12.1 Wooden areas are only to be shown when considered to be of significance to aerial navigation

17.7.12.2 Where shown, the approximate northern or southern limits of tree growth shall be indicated by a dashed black line and shall be appropriately labelled.

17.7.13 Date of topographic information

The date of latest information shown on the topographic base shall be indicated in the margin.

17.8 Magnetic variation

17.8.1 Isogonic lines shall be shown.

17.8.2 The date of the isogonic information shall be indicated in the margin.

17.9 Aeronautical data

17.9.1 General

Aeronautical information shall be shown consistent with the use of a chart and the revision cycle.

17.9.2 Aerodromes

17.9.2.1 Land and water aerodromes and heliports shall be shown with their names, to the extent that they do not produce undesirable congestion on a chart, priority being given to those of greatest aeronautical significance.

17.9.2.2 The aerodrome elevation, the lighting available, the type of runway surface and the length of the longest runway or channel, shown in abbreviated form for each aerodrome in conformity with the example given in ICAO Annex 4, Appendix 2, provided they do not cause undesirable clutter on a chart, shall be indicated.

17.9.2.3 Abandoned aerodromes which are still recognisable as aerodromes from the air shall be shown and identified as abandoned.



17.9.3 Obstacles

17.9.3.1 Obstacles shall be shown.

Note: Objects of a height of 100 m (300 ft) or more above ground are to be regarded as obstacles.

17.9.3.2 When considered of importance to visual flight, prominent transmission lines, permanent cable car installations and wind turbines, which are obstacles, shall be shown.

17.9.4 Prohibited, restricted and danger areas Prohibited, restricted and danger areas shall be shown.

17.9.5 Air traffic services system

17.9.5.1 Significant elements of the air traffic services system including, where practicable, control zones, aerodrome traffic zones, control areas, flight information regions and other airspaces in which VFR flights operate shall be shown together with the appropriate class of airspace.

17.9.5.2 Where appropriate, the air defence identification zone (ADIZ) shall be shown and properly identified.

17.9.6 Radio navigation aids

Radio navigation aids shall be shown by the appropriate symbol and named, but excluding their frequencies, coded designators, times of operation and other characteristics unless any or all of this information which is shown is kept up to date by means of new editions of a chart.

17.9.7 Supplementary information

17.9.7.1 Aeronautical ground lights together with their characteristics or their identifications or both shall be shown.

17.9.7.2 Marine lights on outer prominent coastal or isolated features of not less than 28 km (15 NM) visibility range shall be shown:

- (a) where they are not less distinguishable than more powerful marine lights in the vicinity;
- (b) where they are readily distinguishable from other marine or other types of lights in the vicinity of built-up coastal areas;
- (c) where they are the only lights of significance available.



This Page Intentionally Left Blank

**CHAPTER 18****AERONAUTICAL NAVIGATION CHART — ICAO SMALL SCALE****18.1 Function**

18.1.1 This chart shall:

- (a) serve as an air navigation aid for flight crews of long-range aircraft at high altitudes;
- (b) provide selective checkpoints over extensive ranges for identification at high altitudes and speeds, which are required for visual confirmation of position;
- (c) provide for continuous visual reference to the ground during long-range flights over areas lacking radio or other electronic navigation aids, or over areas where visual navigation is preferred or becomes necessary;
- (d) provide a general purpose chart series for long-range flight planning and plotting.

18.2 Availability

The Aeronautical Navigation Chart — ICAO Small Scale shall be made available in the manner prescribed in 1.3.2 for all areas delineated in ICAO Annex 4, Appendix 5.

18.3 Coverage and scale

18.3.1 When produced, the Aeronautical Navigation Chart — ICAO Small Scale shall provide, as a minimum, complete coverage of the major land masses of the world.

18.3.2 The scale shall be in the range of 1:2,000,000 to 1:5,000,000.

18.3.3 The scale of a chart shall be substituted in the title for the words “Small Scale”.

18.3.4 Linear scales for kilometres and nautical miles arranged in the following order:

- kilometres,
- nautical miles,

with their zero points in the same vertical line shall be shown in the margin.

18.3.5 The length of the linear scale should be not less than 200 mm (8 in).

18.3.6 A conversion scale (metres/feet) shall be shown in the margin.

18.4 Format

18.4.1 The title and marginal notes shall be in English.

18.4.2 The information regarding the number of the adjoining sheets and the unit of measurement to express elevations shall be so located as to be clearly visible when the sheet is folded.



18.5 Projection

18.5.1 A conformal (orthomorphic) projection shall be used.

18.5.1.1 The name and basic parameters of the projection shall be shown in the margin.

18.5.2 Parallels shall be shown at intervals of 1°.

18.5.2.1 Graduations on the parallels shall be shown at sufficiently close intervals compatible with the latitude and the scale of a chart.

18.5.3 Meridians shall be shown at intervals compatible with the latitude and the scale of a chart.

18.5.3.1 Graduations on the meridians shall be shown at intervals not exceeding 5'.

18.5.4 The graduation marks shall extend away from the Greenwich Meridian and from the Equator.

18.5.5 All meridians and parallels shown shall be numbered in the borders of a chart. In addition, when required, meridians and parallels shall be numbered within the body of a chart in such a manner that they can be readily identified when a chart is folded.

18.6 Culture and topography

18.6.1 Built-up areas

18.6.1.1 Cities, towns and villages shall be selected and shown according to their relative importance to visual air navigation.

18.6.1.2 Cities and towns are of sufficient size, they are to be indicated by the outline of their built-up areas and not of their established city limits.

18.6.2 Railroads

18.6.2.1 All railroads having landmark value shall be shown.

18.6.3 Highways and roads

18.6.3.1 Road systems shall be shown in sufficient detail to indicate significant patterns from the air.

18.6.3.2 Roads are not to be shown in built-up areas unless they can be distinguished from the air as definite landmarks.

18.6.4 Landmarks

Natural and cultural landmarks, such as bridges, prominent transmission lines, permanent cable car installations, mine structures, forts, ruins, levees, pipelines, rocks, bluffs, cliffs, sand dunes, isolated lighthouses and lightships, are to be shown only when they are considered to be of importance for visual air navigation.



18.6.5 Political boundaries

International boundaries shall be shown. Un-demarcated and undefined boundaries shall be distinguished by descriptive notes.

18.6.6 Hydrography

18.6.6.1 All water features compatible with the scale of a chart comprising shore lines, lakes, rivers and streams (including those non-perennial in nature), salt lakes, glaciers and ice caps shall be shown.

18.6.6.2 The tint covering large open water areas shall be kept very light.

18.6.6.3 Reefs and shoals, including rocky ledges, tidal flats, isolated rocks, sand, gravel, stone and all similar areas, are to be shown by symbols when of significant landmark value.

18.6.7 Contours

18.6.7.1 Contours shall be shown. The selection of intervals shall be governed by the requirement to depict clearly the relief features required in air navigation.

18.6.7.2 The values of the contours used shall be shown.

18.6.8 Hypsometric tints

18.6.8.1 When hypsometric tints are used, the range of elevations for the tints shall be shown.

18.6.8.2 The scale of the hypsometric tints used on a chart shall be shown in the margin.

18.6.9 Spot elevations

18.6.9.1 Spot elevations shall be shown at selected critical points. The elevations selected shall always be the highest in the immediate vicinity and shall generally indicate the top of a peak, ridge, etc. Elevations in valleys and at lake surface levels which are of value to visual air navigation shall be shown. The position of each selected elevation shall be indicated by a dot.

18.6.9.2 The elevation (in metres or feet) of the highest point on a chart and its geographical position to the nearest five minutes shall be indicated in the margin.

18.6.10 Incomplete or unreliable relief

18.6.10.1 Areas that have not been surveyed for contour information shall be labelled “Relief data incomplete”.

18.6.10.2 Charts on which spot elevations are generally unreliable shall bear a warning note prominently displayed on the face of a chart in the colour used for aeronautical information, as follows:

“Warning — The reliability of relief information on this chart is doubtful and elevations should be used with caution.”



18.6.11 Escarpments

Not applicable

18.6.12 Wooded areas

Wooded areas of large extent are only to be shown when considered to be of significance to aerial navigation

18.6.13 Date of topographic information

The date of latest information shown on the topographic base shall be indicated in the margin.

18.6.14 Colours

18.6.14.1 Subdued colours are to be used for a chart background to facilitate plotting.

18.6.14.2 Good colour contrast is to be ensured to emphasize features important to visual air navigation.

18.7 Magnetic variation

18.7.1 Isogonic lines shall be shown.

18.7.2 The date of isogonic information shall be indicated in the margin.

18.8 Aeronautical data

18.8.1 Aerodromes

Land and water aerodromes and heliports shall be shown with their names, to the extent that they do not produce undesirable congestion on a chart, priority being given to those of greatest aeronautical significance.

18.8.2 Obstacles

Obstacles shall be shown.

18.8.3 Prohibited, restricted and danger areas

Prohibited, restricted and danger areas shall only be shown when considered to be of importance to air navigation.

18.8.4 Air traffic services system

18.8.4.1 Significant elements of the air traffic services system shall only be shown when considered to be of importance to air navigation.

18.8.4.2 Where appropriate, an air defence identification zone (ADIZ) shall be shown and properly identified.



18.8.5 Radio navigation aids

Note: When added to a chart, radio aids to navigation shall only be shown by the appropriate symbol and named.



This Page Intentionally Left Blank



CHAPTER 19

PLOTTING CHART — ICAO

19.1 Function

This chart shall provide a means of maintaining a continuous flight record of the aircraft position by various fixing methods and dead reckoning in order to maintain an intended flight path.

19.2 Availability

When required, this chart is to be made available, in the manner prescribed in 1.3.2, to cover major air routes over oceanic areas and sparsely settled areas used by international civil aviation.

Note: In areas where the Enroute Chart — ICAO is provided, there may be no requirement for a plotting chart.

19.3 Coverage and scale

19.3.1 Where practicable, a chart for a particular region is to cover major air routes and their terminals on a single sheet.

19.4 Format

Where possible, sheets shall be of a size that can be adapted for use on a navigator's plotting table.

19.5 Projection

19.5.1 A conformal projection on which a straight line approximates a great circle shall be used.

19.5.2 Parallels and meridians shall be shown.

19.5.2.1 The intervals should be arranged to permit accurate plotting to be carried out with a minimum of time and effort.

19.5.2.2 Graduation marks shall be shown at consistent intervals along an appropriate number of parallels and meridians. The interval selected shall, regardless of scale, minimise the amount of interpolation required for accurate plotting.

19.5.2.3 Parallels and meridians should be numbered so that a number appears at least once every 15 cm (6 in) on the face of a chart.

19.5.2.4 If a navigational grid is shown on charts covering the higher latitudes, it shall comprise lines parallel to the Meridian or anti-Meridian of Greenwich.

19.6 Identification

Each sheet shall be identified by chart series and number.

19.7 Culture and topography

19.7.1 Generalised shore lines of all open water areas, large lakes and rivers shall be shown.



19.7.2 Spot elevations for selected features constituting a hazard to air navigation shall be shown.

19.7.3 Particularly hazardous or prominent relief features should be emphasised.

Note: Large cities and towns may be shown.

19.8 Magnetic variation

19.8.1 Isogonals or, in higher latitudes, isogrivs, or both, shall be shown at consistent intervals throughout a chart. The interval selected shall, regardless of scale, minimise the amount of interpolation required.

19.8.2 The date of the isogonic information shall be shown.

19.9 Aeronautical data

19.9.1 The following aeronautical data shall be shown:

- (a) aerodromes regularly used by international commercial air transport together with their names;
- (b) selected radio aids to navigation that will contribute to position-finding together with their names and identifications;
- (c) lattices of long-range electronic aids to navigation, as required;
- (d) boundaries of flight information regions, control areas and control zones necessary to the function of a chart;
- (e) designated reporting points necessary to the function of a chart;
- (f) ocean station vessels.

Note: Other aeronautical data may be shown provided that they do not detract from the legibility of essential information.

19.9.2 Aeronautical ground lights and marine lights useful for air navigation should be shown where other means of navigation are non-existent.



CHAPTER 20

ELECTRONIC AERONAUTICAL CHART DISPLAY — ICAO

20.1 Function

The Electronic Aeronautical Chart Display — ICAO, with adequate back-up arrangements and in compliance with the requirements of Annex 6 for charts, shall enable flight crews to execute, in a convenient and timely manner, route planning, route monitoring and navigation by displaying required information.

20.2 Information available for display

20.2.1 The Electronic Aeronautical Chart Display — ICAO shall be capable of displaying all aeronautical, cultural and topographic information required by Chapter 5 and Chapters 7 through 19.

20.3 Display requirements

20.3.1 Display categories

20.3.1.1 Information available for display shall be subdivided into the following categories:

- (a) basic display information, permanently retained on the display and consisting of the minimum information essential for the safe conduct of flight; and
- (b) other display information, which may be removed from the display or displayed individually on demand, and consisting of information not considered essential for the safe conduct of flight.

20.3.1.2 It shall be a simple function to add or remove other display information but shall not be possible to remove information contained in the basic display.

20.3.2 Display mode and generation of neighbouring area

20.3.2.1 The Electronic Aeronautical Chart Display — ICAO shall be capable of continuously plotting the aircraft's position in a true motion mode where reset and generation of the surrounding area shall take place automatically.

20.3.2.2 It shall be possible manually to change a chart area and the position of the aircraft relative to the edge of the display.

20.3.3 Scale. It shall be possible to vary the scale at which a chart is displayed.

20.3.4 Symbols

Symbols used shall conform to those specified for electronic charts in ICAO Annex 4, Appendix 2 — ICAO Chart Symbols except where it is desired to show items for which no ICAO chart symbol is provided. In these cases, electronic chart symbols shall be chosen which:

- (a) employ a minimum use of lines, arcs and area fills;



- (b) do not cause confusion with any existing aeronautical chart symbol;
- (c) do not impair the legibility of the display.

20.3.5 Display hardware

- 20.3.5.1 The effective size of a chart presentation shall be sufficient to display the information required by 20.2 without excessive scrolling.
- 20.3.5.2 The display shall have the capabilities required to accurately portray required elements of ICAO Annex 4, Appendix 2 — ICAO Chart Symbols.
- 20.3.5.3 The method of presentation shall ensure that the displayed information is clearly visible to the observer in the conditions of natural and artificial light experienced in the cockpit.
- 20.3.5.4 The display luminance shall be adjustable by the flight crew.

20.4 Provision and updating of data

- 20.4.1 The provision and updating of data for use by the display shall be in conformance with the aeronautical data quality system requirements.
- 20.4.2 The display shall be capable of automatically accepting authorised updates to existing data. A means of ensuring that authorised data and all relevant updates to that data have been correctly loaded into the display shall be provided.
- 20.4.3 The display shall be capable of accepting updates to authorised data entered manually with simple means for verification prior to final acceptance of the data. Updates entered manually shall be distinguishable on the display from authorised data and its authorised updates and shall not affect display legibility.
- 20.4.4 A record shall be kept of all updates, including date and time of application.
- 20.4.5 The display shall allow the flight crew to display updates so that the flight crew may review the contents of the updates and determine that they have been included in the system.

20.5 Performance tests, malfunction alarms and indications

- 20.5.1 A means shall be provided for carrying out on-board tests of major functions. In case of a failure, the test shall display information to indicate which part of the system is at fault.
- 20.5.2 A suitable alarm or indication of system malfunction shall be provided.

20.6 Back-up arrangements

- 20.6.1 To ensure safe navigation in case of a failure of the Electronic Aeronautical Chart Display — ICAO, the provision of adequate back-up arrangements shall include:
 - (a) facilities enabling a safe takeover of display functions in order to ensure that a failure does not result in a critical situation; and
 - (b) a back-up arrangement facilitating the means for safe navigation of the remaining part of the flight.

**CHAPTER 21****ATC SURVEILLANCE MINIMUM ALTITUDE CHART — ICAO****21.1 Function**

- 21.1.1 This supplementary chart shall provide information that will enable flight crews to monitor and cross-check altitudes assigned by a controller using an ATS surveillance system.
- 21.1.2 A note indicating that a chart may only be used for cross-checking of altitudes assigned while the aircraft is identified shall be prominently displayed on the face of a chart.

21.2 Availability

The ATC Surveillance Minimum Altitude Chart — ICAO shall be made available, in the manner prescribed in 1.3.2, where vectoring procedures are established and minimum vectoring altitudes cannot be shown adequately on the Area Chart — ICAO, Standard Departure Chart — Instrument (SID) — ICAO or Standard Arrival Chart — Instrument (STAR) — ICAO.

21.3 Coverage and scale

- 21.3.1 The coverage of a chart shall be sufficient to effectively show the information associated with vectoring procedures.
- 21.3.2 A chart shall be drawn to scale.
- 21.3.3 Charts shall be drawn to the same scale as the associated Area Chart — ICAO.

21.4 Projection

- 21.4.1 Where possible a conformal projection on which a straight line approximates a geodesic line shall be used.
- 21.4.2 Where shown, graduation marks shall be placed at consistent intervals along the neat lines, as appropriate.

21.5 Identification

A chart shall be identified by the name of the aerodrome for which the vectoring procedures are established or, when procedures apply to more than one aerodrome, the name associated with the airspace portrayed.

21.6 Culture and topography

- 21.6.1 Generalised shorelines of all open water areas, large lakes and rivers shall be shown except where they conflict with data more applicable to the function of a chart.
- 21.6.2 Appropriate spot elevations and obstacles shall be shown.

21.7 Magnetic variation

The average magnetic variation of the area covered by a chart shall be shown to the nearest degree.



21.8 Bearings, tracks and radials

21.8.1 Bearings, tracks and radials shall be magnetic, except as provided for in 21.8.2.

21.8.2 Where bearings, tracks or radials are given with reference to True North or Grid North, this shall be clearly indicated. When Grid North is used, its reference grid meridian shall be identified.

21.9 Aeronautical data

21.9.1 Aerodromes

21.9.1.1 All aerodromes that affect the terminal routings shall be shown. Where appropriate, a runway pattern symbol shall be used.

21.9.1.2 The elevation of the primary aerodrome to the nearest metre or foot shall be shown.

21.9.2 Prohibited, restricted and danger areas Prohibited, restricted and danger areas shall be depicted with their identification.

21.9.3 Air traffic services system

21.9.3.1 A chart shall show components of the established air traffic services system including:

- (a) relevant radio navigation aids together with their identifications;
- (b) lateral limits of relevant designated airspace;
- (c) relevant significant points associated with standard instrument departure and arrival procedures;
- (d) transition altitude, where established;
- (e) information associated with vectoring including:
 - (1) minimum vectoring altitudes to the nearest higher 50 m or 100 ft, clearly identified;
 - (2) lateral limits of minimum vectoring altitude sectors normally defined by bearings and radials to/from radio navigation aids to the nearest degree or, if not practicable, geographical coordinates in degrees, minutes and seconds and shown by heavy lines so as to clearly differentiate between established sectors;
 - (3) distance circles at 20-km or 10-NM intervals or, when practicable, 10-km or 5-NM intervals shown as fine dashed lines with the radius indicated on the circumference and centred on the identified aerodrome main VOR radio navigation aid or, if not available, on the aerodrome/heliport reference point;
 - (4) notes concerning correction for low temperature effect, as applicable;
- (f) communications procedures including call sign(s) and channel(s) of the ATC unit(s) concerned.



The Director General, in exercise of the powers conferred by Section 17(1) of the Civil Aviation Authority Bahamas Act, 2021 (*No. 2 of 2021*) hereby issues the foregoing amended regulation.

Issued the 1st day of July 2021

Electronic Signature
for
Alexander B. Ferguson

**(for) DIRECTOR GENERAL
CIVIL AVIATION AUTHORITY BAHAMAS**



This Page Intentionally Left Blank